

#### DESCRIPTION:

The IX-DF-2RA-FR is an IP addressable stainless steel, flush mount video door station with standard and emergency call buttons. Both buttons feature appropriate French signage. Call status indicators are included to meet rescue assistance requirements.

The emergency button will trigger two programmable relay outputs for activation of external systems or devices and can be programmed to call a different master station than the standard call button.

The built-in camera provides an 87° viewing angle. The unit has a stainless steel faceplate and includes tamper resistant screws.

The IX-DF-2RA-FR is compatible with the IX Series. Each station can be assigned one of three priority call queuing levels. The station is 802.3af PoE compliant.

Flush mount with supplied back box or surface mount with the SBX-ISDVFRA.

#### FEATURES:

- Audio communication and visual identification of calling area
- Two call buttons: Standard and Emergency
- LED call status indicator
- Red mushroom button for emergency call
- Stainless steel faceplate with tamper resistant screws
- ONVIF Profile S compliant



# IX-DF-2RA-FR

IP Addressable Dual-Call Button Video Emergency Station with French Signage for the IX Series

## FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] Call status indicators
- [4] Speaker
- [5] Call button
- [6] LED locator
- [7] Appel signage
- [8] Emergency button
- [9] Urgence signage

## SPECIFICATIONS:

- Power Source: 802.3af PoE compliant
- Communication: Open voice, hands-free
- Camera: 1/4" color CMOS VGA
- Min. illumination: 5 Lux
- Wiring: CAT-5e or CAT-6
- Wiring distance: 330'
- Door release: 24V AC/DC, 500mA  
(N/O, COM, N/C)
- Operating Temp: 14° - 140°F (-10° - 60°C)
- Ingress Protection: IP55
- Dimensions: 11-11/16"H x 7" W

## FEATURE CALL-OUTS:

