

NVR4 Workstation

4th Generation





Avigilon's high-performance NVR Workstations are configured to enable standalone viewing and recording from a single machine, making them ideal for simple deployments that do not require enterprise-grade alternatives. Invest in the right-sized solution for your organization with an all-in-one high-performance solution that offers scalability for both small sites and large systems.



Features



4K SUPPORT*

Supports full 4K video streaming for monitoring high resolution cameras.

* ACC™ Client software at 200% DPI scaling.



RECOVERY PARTITION

Supplies an Avigilon recovery partition for restoring default settings in the event of system issues without the need for external hardware or an internet connection.



SMALL FORM FACTOR

Offers the flexibility of a small form factor for ease of installation in all applications.



SOLID STATE DRIVE

Provides the operating system on a solid-state drive, which seperates the OS from the video data drive for greater reliability.

Specifications

SYSTEM				4K* × 2 displays	HD × 2 displays	
	Network Video	Recording Data Rate		Up to 120 Mbps		
	Streaming Performance	Playback and Live Streaming		Up to 100 Mbps		
	Primary Stream Performance (ACC software set to high quality)		2MP	20 Streams	20 Streams	
		15 FPS	4MP	14 Streams	14 Streams	
			8MP	8 Streams	8 Streams	
		30 FPS	2MP	10 Streams	14 Streams	
			4MP	8 Streams	9 Streams	
			8MP	4 Streams	4 Streams	
	Supported Mon	nitor Interfaces		Combination of up to 2: mDP, DP, and HDMI (DP and HDMI adapters are supplied)		
	Operating System			Microsoft® Windows 10 IoT Enterprise LTSB		
	Video Data Drive			1 SATA drive, 4 TB or 8 TB		
	OS Drive			256 GB M.2 SSD		
	Processor			Intel® Core™ i3		
	Memory			8 GB DDR4 RAM		
	Network Interface			2 × 1 GbE RJ-45 ports (1000Base-T)		
	Video Outputs			2 Active (4 × mini DisplayPort)		
	Optical Drive			DVD-RW		
	Avigilon Control Center™ Edition			Enterprise, Standard or Core compatible * ACC Client software at 200% DPI scaling.		
MECHANICAL	Form Factor			Small form factor		
	Dimensions (WxHxD)			292 mm × 92.6 mm × 290 mm (11.50" × 3.65" × 11.42")		
	Weight			5.26 kg (11.57 lbs)		
ELECTRICAL	Power Input			100 to 240 VAC, 50/60 Hz, auto-switching		
LLLOTRICAL	Power Supply			Single non-redundant		
	Power Consumption			260 W		
	Tower demounipation			1250 11		
ENVIRONMENTAL	Operating Temperature			10° C to 35° C (50° F to 95° F)		
	Storage Temperature			-40° C to 65° C (-40° F to 149° F)		
	Humidity			5% to 95% relative humidity with 33 °C (91 °F) maximum dew point (non-condensing)		
	Operating Vibration			0.26 Grms at 5 Hz to 350 Hz		
	Storage Vibration			1.88 Grms at 10 Hz to 500 Hz for 15 minutes		
	Operating Shock			Shock pulse of 40 G for up to 2.3 ms		
	Storage Shock			Shock pulse of 71 G for up to 2.0 ms		
	Operating Altitude			-15.2 m to 3048 m (-50 ft to 10,000 ft)		
	Storage Altitude			-15.2 m to 12,000 m (-50 ft to 39,370 ft)		
SUPPLIED ACCESSORIES	USB Keyboard, USB Mouse, Power cord, 2 mDP to DP adapters, 2 mPD to HDMI adapters					
CERTIFICATIONS	Certifications/D	irectives		UL, cUL, CE, RCM, CCC, KC, VCCI, EAC, BSMI, N	IOM, RoHS, Reach (SVHC)	
	Safety			EN/IEC 62368-1		
	Electromagnetic Emissions			CFR Title 47, FCC Part 2, 15 Class B, ICES-003, EN 55032 Class B, EN 61000-3-2 (Class D), EN 61000-3-3		
	Electromagnetic Immunity			EN 55024		
	Warranty			Lifetime 24/7 Avigilon technical phone support and a 3 year next business day warranty		
					, , , , , , , , , , , , , , , , , , , ,	
ORDERING	NVR4-WKS-4TB			NVR4 Workstation, 4.0 TB Storage		
INFORMATION	NVR4-WKS-8TB			NVR4 Workstation, 8.0 TB Storage		
	NVR4-WKS-WARR-EXTEND-1YR					
				2-Year Extended Warranty for NVR4-WKS/RM5-WKS		
	WKS-RACK			Rack compatible with NVR4-WKS/RM5-WKS		
NVR4-WKS-xTB-NA = NVR4-WKS-xTB-UK = NVR4-WKS-xTB-EU = NVR4-WKS-xTB-AU =						