

# AXIS T92G20 Outdoor Housing

Robust and spacious with built-in IR illumination

AXIS T92G20 Outdoor Housing has a robust metal casing with IP66/IP67, NEMA 4X, and IK10 ratings for protection against dust, UV radiation, water and impact. It is spaciouly designed to house cameras with large CS-mount lenses and connecting accessories. With efficient cooling fins and heaters, the housing maintains optimal conditions for sensitive components, and enables cameras to operate in both extremely hot and cold environments. Suitable for fixed box cameras in both indoor and outdoor installations, AXIS T92G20 offers built-in IR illumination for outstanding surveillance in the dark, and PoE connectivity for easy one-cable installation.

- > **Built-in IR illumination**
- > **Efficient heat handling**
- > **Protection against impact, water, dust, UV and corrosion**
- > **Compatible with selected cameras from AXIS Q.16 Series**
- > **Included wall mount**



## AXIS T92G20 Outdoor Housing

General	
<b>Supported products</b>	AXIS Q1645 Network Camera AXIS Q1647 Network Camera
<b>Casing</b>	IP66-, IP67-, NEMA 4X- and IK10-rated Aluminum Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4, max 25.5 W
<b>IR illumination</b>	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 30 m (98 ft) or more depending on the scene
<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) Start-up: -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
<b>Approvals</b>	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, EN 55015, EN 61547
	<b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, IEC/EN 62262 IK10, NEMA 250 Type 4X <b>Other</b> IEC 62471
<b>Weight</b>	5400 g (11.9 lb)
<b>Included accessories</b>	Installation guide, drill hole template, connector kit, Torx® T20 screw driver, sunshield, connector guard, AXIS T94Q01A Wall Mount
<b>Optional accessories</b>	T91 Mounting Accessories, T94 Mounting Accessories, YP3040 PT Motor, Bird Control Spikes, AXIS Door Switch A For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Warranty</b>	Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

### Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)