

AXIS Audio Manager Pro C7050

Your gateway to the world of network audio

AXIS Audio Manager Pro C7050 provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or to all the devices in all zones. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager Pro realizes the benefits of network audio. The AXIS Audio Manager Pro software comes pre-installed on the C7050 server.

- > [One single user interface](#)
- > [Central control](#)
- > [Zone management](#)
- > [Audio content management](#)
- > [Scheduling](#)



AXIS Audio Manager Pro C7050

Processor	Intel® Core™ i3-7100T, 3,4 GHz, 3MB Cache, 2C/4T	Operating conditions	5 °C to 35 °C (41 °F to 95 °F)
Memory	8GB (1x8GB) SO-DIMM 2400 MHz DDR4, non ECC	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Storage	M.2 128 GB SATA Solid State Drive	Approvals	FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KCC KN32 Class B, KN35, EN 62311, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EAC, BSMI, EN 50564, EN 62623, IEC/EN/UL 60950-1
Graphic card	Intel® integrated graphics	Dimensions	182 x 33 x 178 mm (7.2 x 1.4 x 7.0 in)
Operating system	Microsoft Windows 10 IoT 2016 LTSB	Weight	1.17 kg (2.58 lb)
General		Included accessories	Installation guide, power supply with cable, safety and regulatory document
Power	65 W, external power adapter AC Input 90-264 V, 50/60 Hz	Optional accessories	
Connectors	6x External USB 3.1 Gen 1 (2 front/4 rear) 1x RJ45 Ethernet 1x HDMI 1.4 1x Display Port 1.2 1x UAJ (Universal Audio Jack) 1x Audio line out	Warranty	Axis 3-year warranty, see www.axis.com/warranty
Mounting option	VESA 100 x 100 mm (3 15/16 x 3 15/16 in)		

AXIS Audio Manager Pro

General		Network	
	1000+ audio devices	Supported protocols	IPv4, HTTP, DNS, NTP, RTP, RTSP, TCP, UDP, DHCP, SIP, mDNS, M3U
Languages	English, Czech	Security	Multiple user access levels with password protection
Licenses	Unlimited	System integration	
Compatible products	AXIS C1004-E, AXIS C2005, AXIS C3003-E, AXIS C8033, AXIS C8210, AXIS C1310-E, AXIS C1410	Audio streaming	Support for internet radio by URL. Can be connected to Dante using virtual soundcards.
Operating system	Microsoft Windows 10 IoT 2016 LTSB	VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX.
System requirements		Events	
Minimum requirements	Hardware installation: Intel® Core™ i3-7100T Virtual machine support: VMware ESXi, Microsoft Hyper-V, and Microsoft Windows Datacenter with configuration and resources allocated similar to the minimum hardware requirements.	Event triggers	HTTP commands triggering Playback scheduler
Audio		System	
Audio streaming	Stereo/mono from 32 kbps to 320 kbps, unicast or multicast, MPEG-1 Audio Layer 2 (MP2) for internal streaming See avlib audio codec support	Logs	System log, syslog server support
VoIP	G.711u, G.711a	Environmental responsibility: axis.com/environmental-responsibility	