

# AXIS W100 Body Worn Camera

Body worn camera from Axis

AXIS W100 Body Worn Camera is an easy-to-use, lightweight and robust body worn camera with an operating time of over 12 hours at 1080p. It delivers sharp images even in challenging conditions and has dual microphones for excellent audio and noise suppression. AXIS W100 features the Klick Fast System, making it compatible with most available mounting options. In addition, Axis Zipstream technology allows users to store as much footage as they require without compromising image quality. The camera also features a GPS/GNSS receiver for location tracking, Bluetooth Low Energy 4.1, IEEE 802.11b/g/n, and a 6-axis gyro and accelerometer.

- > [Operating time of up to 17 hours](#)
- > [Klick Fast System](#)
- > [WDR](#)
- > [Dual microphones for noise suppression](#)
- > [3 year warranty](#)



## AXIS W100 Body Worn Camera

<b>Camera</b>		Color: NCS S 9000-N
<b>Image sensor</b>	1/2.9" progressive scan RGB CMOS	<b>Mounting</b> Klick Fast System
<b>Lens</b>	Focal length, 2.1 mm Horizontal field of view: 141° Vertical field of view: 83° Fixed iris, F2.1	<b>Sustainability</b> PVC free
<b>Shutter time</b>	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz	<b>Connectors</b> Pogo pin pads, USB Type-C
<b>Video</b>		<b>Operating conditions</b> -20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–100% RH (condensing)
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) High Profile	<b>Storage conditions</b> -20 °C to 45 °C (-4 °F to 113 °F) Humidity 5–95% RH (non-condensing)
<b>Resolution</b>	1920x1080, 1280x720	<b>Approvals</b> EMC EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B
<b>Frame rate</b>	25 fps at 50 Hz 30 fps at 60 Hz	Wireless EN 300328, EN 301489-1, EN 301489-17, EN 303413, FCC Part 15 Subpart C, RSS-247
<b>Wide dynamic range</b>	WDR	Safety IEC/EN 62368-1, EN 50360
<b>Video streaming</b>	Axis Zipstream for body worn	Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP67 MIL-STD-810H (Method 501.7, 503.7, 505.7, 509.7, 512.6, 516.8)
<b>Audio</b>		<b>Dimensions</b> Height: 94 mm (3.7 in) Width: 68 mm (1.7 in) Depth: 27 mm (1.1 in)
<b>Audio compression</b>	AAC-LC 8/16/32/48 kHz	<b>Weight</b> 174 g (0.38 lb)
<b>Audio input/output</b>	Built-in dual microphones	<b>Included accessories</b> AXIS TW1100 Clip Mount
<b>General</b>		<b>Optional accessories</b> Klick Fast System for Body worn camera mounts, AXIS TW1200 Body Worn Mini Bullet Sensor AXIS Body Worn Assistant app for Android, iOS For more accessories, see <a href="http://axis.com/bodyworn">axis.com/bodyworn</a>
<b>Battery</b>	Li-ion, 3600 mAh, up to 17 hours operating time	<b>Warranty</b> Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Storage</b>	64 GB non-volatile memory, up to 30 hours of recorded video AES256 encryption standard	
<b>Positioning system</b>	GPS, Galileo, GLONASS	
<b>Sensor</b>	6-axis gyro and accelerometer	
<b>User interface</b>	Status indicators, audio and vibration feedback	
<b>Wireless interface</b>	Bluetooth Low Energy 4.1 IEEE 802.11b/g/n @ 2.4 GHz channels 1–11	
<b>Cybersecurity</b>	Signed firmware	
<b>Casing</b>	IP67-rated Plastic casing	

Environmental responsibility:  
[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)