

AXIS M3045-WV Network Camera

HDTV 1080p / 2 MP fixed mini dome with HDMI and wireless connection

AXIS M3045-WV is an affordably priced indoor fixed dome that provides HDTV 1080p video. The camera connects to the network over wireless LAN or over Ethernet with an integrated RJ45 connector. WDR ensures that details in both the dark and bright areas of a scene are visible. HDMI support enables live streaming to an HDTV monitor for e.g. public viewing. The factory-focused camera can be mounted on walls or ceilings and with its 3-axis camera angle adjustment it can be easily leveled and directed in any direction. Axis' Corridor Format enables vertically oriented video streams. AXIS M3045-WV supports video analytics such as people counting.

- > **Ultra-compact, vandal and dust-resistant design**
- > **Connects over wireless LAN or Ethernet**
- > **HDMI support enables streaming to a monitor**
- > **Axis' Zipstream technology for reduced bandwidth and storage**
- > **Axis' Corridor Format**



AXIS M3045-WV Network Camera

Camera		Data streaming	Event data
Image sensor	1/3" progressive scan RGB CMOS	Built-in installation aids	Pixel counter
Lens	M12 mount, Fixed iris, Fixed focus 2.8 mm, F2.0 Horizontal field of view: 106° Vertical field of view: 59°	General	
Light sensitivity	0.25 lux at 50 IRE F2.0	Casing	Color: White NCS S 1002-B (For repainting of cover, remove the transparent dome. Contact your Axis partner for repainting instructions), Encapsulated electronics, Captive screws (Torx 10), IP42 water- and dust-resistant (to comply with IP42, follow Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing
Shutter time	1/32500 s to 1/5 s	Sustainability	PVC free
Camera angle adjustment	Pan $\pm 177^\circ$, Tilt $\pm 69^\circ$, Rotation $\pm 176^\circ$ Can be directed in any direction and see the wall/ceiling	Memory	512 MB RAM, 256 MB Flash
Video		Power	4.8–5.2 V DC Typical 2.7 W, max. 3.1 W
Video compression	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profiles, Motion JPEG	Connectors	RJ45 10BASE-T/100BASE-TX Micro USB for DC power HDMI Type D
Resolutions	1920x1080 (1080p) to 320x240	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For memory card and NAS recommendations see www.axis.com
Frame rate	25/30 fps with power line frequency 50/60 Hz	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 15–85% RH (non-condensing)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, Axis' Zipstream technology in H.264, VBR/MBR H.264 HDMI	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	Approvals	EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, IEC/EN/UL 60950-1, EN 300328, EN 301489-1, EN 301489-17, EN 301893, FCC Part 15 Subpart C, FCC Part 15 Subpart E, RSS-247 IEC/EN 60529 IP42, IEC/EN 62262 Class IK08
Pan/Tilt/Zoom	Digital PTZ	Dimensions	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
HDMI output	HDMI 1080p@25/30 fps (50/60 Hz) HDMI 1080i@50/60 fps (50/60 Hz) HDMI 720p@50/60 fps (50/60 Hz) HDMI 720p@25/30 fps (50/60 Hz)	Weight	170 g (0.38 lb)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, WDR, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Included accessories	Power supply, Installation Guide, Windows decoder 1-user license, Torx L-key
Network		Optional accessories	AXIS T94B02D Pendant kit AXIS T94B02L Recessed mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate View protection Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see www.axis.com
Wireless interface	Internal antenna IEEE 802.11 a/b/g/n, 2.4 and 5 GHz	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Security	Password protection, IP address filtering, HTTPS ³ encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management WEP 64/128 bit, WPA/WPA2-PSK, WPA, WPA2 Enterprise WLAN pairing button (Wi-Fi Protected Setup™ PBC compatible)	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI 1.4b	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
System integration		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Environmental responsibility: www.axis.com/environmental-responsibility	
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap		
Event triggers	Analytics, Edge storage events		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering Overlay text		