

AXIS Q1659 Network Camera

Professional photography meets video surveillance

AXIS Q1659 offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances. It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes. AXIS Q1659 is compatible with a large number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.

- > [20 MP resolution](#)
- > [Canon EF mount and EF/EF-S lenses](#)
- > [Axis' Zipstream technology](#)
- > [PoE and SFP slot for optional fiber connection](#)
- > [Optional accessory housing](#)



AXIS Q1659 Network Camera

Models	<p>AXIS Q1659 24 mm, f/2.8 AXIS Q1659 35 mm, f/2 AXIS Q1659 50 mm, f/1.4 AXIS Q1659 85 mm, f/1.2L AXIS Q1659 100 mm, f/2.8L AXIS Q1659 10–22 mm, f/3.5–4.5 AXIS Q1659 70–200 mm, f/2.8L</p>	Analytics	<p>Included AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap</p>
Camera		Event triggers	Analytics, edge storage events, external input
Image sensor	22.4 x 15.0 mm APS-C CMOS-sensor	Event actions	<p>File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, send SNMP trap, video and audio recording to edge storage, pre- and post-alarm video buffering, external output activation, day/night vision mode, play audio clip, status LED</p>
Lens	<p>EF/EF-S mount 24 mm, f/2.8 Horizontal field of view: 20MP 50.1°, 4K 36.3° 35 mm, f/2 Horizontal field of view: 20MP 35.5°, 4K 25.4° 50 mm, f/1.4 Horizontal field of view: 20MP 25.3°, 4K 17.9° 85 mm, f/1.2L Horizontal field of view: 20MP 15.0°, 4K 10.6° 100 mm, f/2.8L Horizontal field of view: 20MP 12.8°, 4K 9.0° 10–22 mm, f/3.5–4.5 Horizontal field of view: 20MP 96.6°– 54.0°, 4K 76.4°– 39.4° 70–200 mm, f/2.8L Horizontal field of view: 20MP 18.2°– 6.4°, 4K 12.8°– 4.5°</p>	Data streaming	Event data
Day and night	Automatically removable infrared-cut filter	Built-in installation aids	Pixel counter, remote focus
Minimum illumination	<p>Color: 0.04 lux F1.2 B/W: 0.004 lux F1.2</p>	General	
Shutter time	1/8000 to 1 s	Casing	<p>Camera: Aluminum Color: Black NCS S 9000–N</p>
Pan/Tilt/Zoom	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)	Memory	1 GB RAM, 256 MB Flash
Video		Power	<p>20–28 V DC, max 18.6 W Power over Ethernet IEEE 802.3af/802.3at Type 2 Class 4 Typical 13.1 W, max 25.5 W</p>
Video compression	H.264 (MPEG-4 Part 10/AVC), High, Main and Baseline Profile Motion JPEG	Connectors	<p>RJ45 100BASE-TX/1000BASE-T PoE 3.5 mm mic/line in, 3.5 mm line out DC input Terminal block for 2 configurable inputs/outputs (12 V DC output, max load 50 mA) RS485/RS422 SFP slot (100/1000 Mbps) for SFP fiber module</p>
Resolutions	5472x3648 to 320x240	Storage	<p>Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com</p>
Frame rate	<p>5472x3648 (20 MP): 8 fps Ultra HD 2160p (4K): 25 fps</p>	Operating conditions	<p>0 °C to 45 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)</p>
Video streaming	<p>Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth Axis Zipstream technology in H.264 VBR/CBR H.264</p>	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Multi-view streaming	Up to 4 individually cropped out view areas	Approvals	<p>EMC EN 55032 Class A, EN 50121–4, EN 55024, EN 61000–6–1, EN 61000–6–2, IEC 62236–4, FCC Part 15 Subpart B Class A, ICES–003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950–1</p>
Image settings	Compression, color, brightness, sharpness, white balance, exposure control, fine tuning of behavior at low light, text overlay, privacy mask, rotation: 0°, 180°, day and night shift level	Dimensions	Camera body: 176 x 102 x 75 mm (7 x 4 x 3 in)
Audio		Weight	Camera body: 840 g (1.85 lb)
Audio streaming	Two-way	Included accessories	EF mount cover, connector kit, Installation Guide, Windows decoder 1-user license
Audio compression	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate, OPUS	Optional accessories	Outdoor housing, Axis PoE+ Midspans For more accessories, see www.axis.com
Audio input/output	External microphone or line input, line output	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/support/downloads
Network		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p>	
System integration		Environmental responsibility:	www.axis.com/environmental-responsibility
Application Programming Interface	<p>Open API for software integration, including VAPIX[®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S and G, specification at www.onvif.org</p>		