

## **AXIS T94N01G Pole Mount**

## For sturdy installations on poles

The high-quality AXIS T94N01G Pole Mount is designed for use with Axis positioning cameras and positioning units. It is intended for poles between 100-410 mm (4-16 in) in diameter. AXIS T94N01G has an IK10 rating for impact resistance, which safeguards it against vandalism. It features a closed back and a cable gasket for protection against insect infestation.

- > For indoor and outdoor use
- > Impact-resistant (IK10)
- > Cable gasket to prevent insect infestation
- > Robust and safe
- > Suitable for Axis positioning cameras and positioning units





## **AXIS T94N01G Pole Mount**

General	
Supported products	AXIS T94J01A Wall Mount AXIS T91D62 Telescopic Parapet Mount AXIS T98A-VE Cabinet Series
Casing	Powder coated aluminum Color: white NCS S 1002-B
Sustainability	PVC free
Environment	Indoor Outdoor
Storage conditions	-45 °C to 70 °C (-49 °F to 158 °F)
Approvals	Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment NEMA 250 Type 4x, IEC 62262 IK10, RoHS, REACH, WEEE
Dimensions	49 x 231 x 226 mm (1.9 x 9.1 x 8.9 in)

Weight	1.7 kg (3.7 lb)
Maximum load	25 kg (55.1 lb)
Cable routing	Back: cable hole
Included accessories	Installation Guide Stainless steel straps 1450 mm (57 in), 3 pieces Insect-proof cable gasket for 4 cables Gasket C M20 Set screw
Optional accessories	Stainless steel straps 700 mm (28 in), 1 pair Stainless steel straps 570 mm (22 in), 1 pair For more accessories, see www.axis.com
Warranty	Axis 3-year warranty, see www.axis.com/warranty

Environmental responsibility: www.axis.com/environmental-responsibility

