

D134 Dual Relay Module

www.boschsecurity.com



BOSCH
Invented for life



The D134 provides two Form C dry contacts, each rated for 2 A at 30 VDC.

Certifications and approvals

Region	Certification
USA	UL
	UL 365 - Police Station Connected Burglar Alarm Units
	UL 464 - Standard for Audible Signal Appliances
	UL 609 - Standard for Local Burglar Alarm Units and Systems
	UL 985 - Household Fire Warning System Units
	UL 1023 - Household Burglar Alarm System Units
	UL 1076 - Proprietary Burglar Alarm Units and Systems
	UL 1610 - Central Station Burglar Alarm Units
	UL 1635 - Standard for Digital Alarm Communicator System Units

Region	Certification
	CSFM see our website
	CSFM California Office of The State Fire Marshall

Installation/configuration notes

Control panels	B9512G/B9512G-E B8512G/B8512G-E B6512 B5512/B5512E B4512/B4512E B3512/B3512E Easy Series V3+
Legacy control panels	D6412/D4412 D2212B/D2212BE

Technical specifications

Properties

Dimensions	3.16 in (8 cm) x 1.51 in (3.8 cm) x 9 in (22.8 cm)
------------	--

Wiring

Wiring	Maximum distance – Wire size (unshielded wire only): 50 ft (15.25 m) – 22 AWG (1.02 mm), 75 ft (23 m) – 18 AWG (0.65 mm)
--------	---

Power requirements

Current draw	40 mA per relay
Relay contact rating	2 A at 30 VDC

Ordering information

D134 Dual Relay Module

Provides two Form C dry contacts each rated for 2 A at 30 VDC.

Order number **D134**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia