

# NPD-5004-POE Midspan PoE Injector

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Makes PoE cameras easy to install
- ▶ Allows one-wire connection
- ▶ Reduces power supply requirements
- ▶ Compact and cost effective solution
- ▶ Supplies up to 15.4 W per port

This power injector allows an existing Ethernet infrastructure to be enhanced for use with PoE cameras.

### System overview

The NPD-5004-POE four-port power injector can supply four individual PoE cameras with power.

### Functions

The injector converts the AC input power to a +48 VDC power supply which is then provided to the cameras via the Ethernet cable. They support up to 10/100/1000 Mbps pass-through data rates. Each injector provides up to 15.4 W per port. The PoE midspan injector unit can be easily mounted on a shelf, wall or ceiling

### Certifications and approvals

Standards	
	FCC Part 15, Class B
	EN 60950
	EN 55022 class B
	EN 55024
	IEEE 802.3af

<b>Approvals</b>	UL, cUL, FCC, VCCI, GS mark
<b>Regulatory compliance</b>	CE, RoHS, WEEE,

Region	Certification
Europe	CE

### Parts included

- PoE midspan injector unit
- Power cord

### Technical specifications

Power	
Input supply voltage	100 to 240 VAC; 50/60 Hz
Maximum input current	1 A @ 110 VAC; 0.4 A @ 240 VAC
Output supply voltage	+ 48 VDC nominal
Output port power	15.4 W max.

Input/output	
Power input connector	IEC 60320
Ethernet connection	Shielded RJ45 connector; EIA 568A and 568B
Data	10/100/1000 Mbps pass-through data rates

Mechanical	
Dimensions (W x H x L)	148 x 43 x 224 mm (5.82 x 1.69 x 8.82 in)
Weight	620 g (1.4 lb)

Environmental	
Operating Temperature	0°C to +40°C (32°F to 104°F)
Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Operating Humidity	90% RH max. non-condensing
Storage Humidity	95% RH max. non-condensing
Thermal rating	51 BTU/hour

**Ordering information**

**NPD-5004-POE Midspan PoE Injector**  
 Power-over-Ethernet midspan injectors for use with PoE enabled cameras; 15.4 W, 4-ports  
 Order number **NPD-5004-POE**

**Represented by:**

**North America:**  
 Bosch Security Systems, Inc.  
 130 Perinton Parkway  
 Fairport, New York, 14450, USA  
 Phone: +1 800 289 0096  
 Fax: +1 585 223 9180  
 security.sales@us.bosch.com  
 www.boschsecurity.us

**Europe, Middle East, Africa:**  
 Bosch Security Systems B.V.  
 P.O. Box 80002  
 5617 BA Eindhoven, The Netherlands  
 Phone: + 31 40 2577 284  
 Fax: +31 40 2577 330  
 emea.securitysystems@bosch.com  
 www.boschsecurity.com

**Asia-Pacific:**  
 Robert Bosch (SEA) Pte Ltd, Security Systems  
 11 Bishan Street 21  
 Singapore 573943  
 Phone: +65 6571 2808  
 Fax: +65 6571 2699  
 apr.securitysystems@bosch.com  
 www.boschsecurity.asia

**China:**  
 Bosch (Shanghai) Security Systems Ltd.  
 203 Building, No. 333 Fuquan Road  
 North IBP  
 Changning District, Shanghai  
 200335 China  
 Phone +86 21 22181111  
 Fax: +86 21 22182398  
 www.boschsecurity.com.cn

**Latin America and Caribbean:**  
 Robert Bosch Ltda Security Systems Division  
 Via Anhanguera, Km 98  
 CEP 13065-900  
 Campinas, Sao Paulo, Brazil  
 Phone: +55 19 2103 2860  
 Fax: +55 19 2103 2862  
 latam.boschsecurity@bosch.com  
 www.boschsecurity.com