

# AL300ULXR Power supply with cord, 2.5A 12/24V

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Single-output power supply
- ▶ Regulated 12 VDC or 24 VDC selectable output
- ▶ Filtered and electronically-regulated output
- ▶ Short-circuit and thermal-overload protection
- ▶ Built-in charger for sealed lead-acid or gel type batteries

The AL300ULXR is a power supply/charger that converts a 115 VAC/60 Hz input into a single Class 2 rated 12 VDC or 24 VDC power-limited output.

## Functions

### Supervision

- AC fail supervision through Form C contacts with notification triggered selectable for 30 seconds (factory setting) or 6 hours
- Low battery supervision through Form C contacts
- Battery presence supervision through Form C contacts

### Visual indicators

LED indicators for AC input, DC output, and battery

## Certifications and approvals

Region	Regulatory compliance/quality marks	
USA	UL	UL 603, Power Supplies for Use with Burglar-Alarm Systems
	UL	UL 1481, Power Supplies for Fire-Protective Signaling Systems

Region	Regulatory compliance/quality marks	
	CSFM	see www.boschsecurity.com (the Bosch website)
	NYC-MEA	MEA 168-92-E Vol. 12
Canada	ULC	ULC-S318, Power Supplies for Burglar Alarm Systems
	ULC	CSA-C22.2 No. 205, Signal Equipment

## Parts included

Quantity	Component
1	Power supply/charger
1	Enclosure
1	Hardware pack
1	Installation manual

## Technical specifications

### Electrical

Inputs	115 VAC, 60 Hz, 3.5 A
Fuse rating	5 A at 250 V

### Environmental

<b>Temperature</b>	
Operating	+32°F to +120°F (0°C to +49°C)
Storage	-4°F to +158°F (20°C to 70°C)
Relative humidity	85% ± 5%
BTU/hour (approximate)	
12 VDC	15 BTU/hour
24 VDC	31 BTU/hour

### Mechanical

Enclosure* dimensions (HxWxD)	13.5 in. x 13 in. x 3.25 in. (343 mm x 330 mm x 83 mm)
<b>Weight (without batteries)</b>	
Product	6.65 lbs. (3.1 kg)
Shipping	8.45 lbs. (3.83 kg)

\* Enclosure is wall mounted indoors and accommodates up to two 12 VDC/7 Ah batteries. It has combination 0.5 in. (12.7 mm) and 0.75 in. (19.1 mm) knockouts.

### Trademarks

All hardware/software product names used in this document are likely to be registered trademarks and must be treated accordingly.

### Ordering information

#### AL300ULXR Power supply with cord, 2.5A 12/24V

A power supply/charger that converts 115 VAC/60 Hz input into a single Class 2 (12 VDC or 24 VDC) power-limited output

Order number **AL300ULXR**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia