



ARD-AYH12 - RFID Proximity Reader



- ▶ Reader with beeper and multicolored LED display
- ▶ Wiegand output for EM
- ▶ Indoor and outdoor mounting

Certifications and Approvals

USA: UL 294 & FCC Part 15B

Europe: CE

Installation/Configuration Notes

The ARD-AYH12 is supplied with an 18 inch (45 cm) pigtail. The table below shows how to wire the reader to the controller.

COLOR	WIEGAND OUTPUT
Red	DC + Input
Black	Ground
White	Data 1
Green	Data 0
Brown	LED Control
Purple	Tamper

Note When using a separate power supply for the reader, this supply and the cable shield wire on the reader should be attached to an earth ground (best) or signal ground connection at the panel or power supply end of the cable.

Technical Specifications

Electrical Characteristics

Power supply type	Linear type recommended
Operating voltage range	5 – 16 VDC
Maximum input current	Standby: 35 mA Read: 100 mA
Tamper output	Open collector, active low, max. sink current 16 mA
RF modulation	ASK

Ranges

Max. cable distance to controller	500 ft. (150 m)
Operating temperature range	-25°F to 145 °F (-31 °C to 63 °C)
Operating humidity	0 to 95% (non condensing)
Read range *	4.72 inch (12 cm)
Dimensions (H x W x D)	4.33 x 2.95 x 0.59 inch (110 x 75 x 15 mm)

* The reading range depends on card type, electrical environment, and/or proximity to metal.

Ordering Information**ARD-AYH12 - RFID Proximity Reader** **ARD-AYH12**

Access control card reader with Wiegand output for 125 kHz card technology (EM).

Accessories**ACD-ATR11ISO - RFID Card** **ACD-ATR11ISO**

Standard 125 kHz proximity read-only card for Wiegand readers type W 3. Packing information: 25 cards/ each unit

ACD-ATR14CS - RFID Card **ACD-ATR14CS**

Clamshell standard 125 kHz proximity read-only card for Wiegand readers type W 3. Packing information: 25 clam shell cards/ each unit

ACA-ATR13 - RFID Tag **ACA-ATR13**

125 kHz proximity read-only tag for Wiegand readers type W 3. Packing information: 25 tags/ each unit

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by