

D126 Standby Battery (12 V, 7 Ah)

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 12 VDC sealed lead-acid
- ▶ Fully rechargeable
- ▶ Maintenance-free
- ▶ For use as secondary power source
- ▶ Long service life

This battery is a maintenance-free, sealed lead-acid, standby and auxiliary power source that provides long service life and dependability.

The battery is for use only with charging circuits calibrated for lead-acid batteries. It is suitable for supplying backup power for fire, security, and access control systems during AC power failures.

The D126 fits in any of the currently offered enclosures and connects to the two color-coded battery leads supplied with the control panel or module. Use a D122 Dual Battery Harness to connect two D126 batteries in parallel and double the amp hour capacity.

Certifications and approvals

Region	Certification
USA	CSFM California State Fire Marshal (see our website)

Installation/configuration notes

Standby power requirements

Refer to the appropriate control panel installation manual for information on calculating the standby battery requirements for the system. Total continuous and intermittent current requirements must not exceed the amp hour capacity of the battery.

Compatibility

The battery is compatible with all Bosch control panels.

Parts included

Quantity	Component
1	12 V battery

Technical specifications

Capacity

Capacity (25 °C)	12 V, 7.2 Ah	20 hour rate
Internal resistance	Fully charged battery (25 °C)	21 MΩ
Temperature dependency of capacity (20 hour rate)	40 °C (104 °F)	102%
	25 °C (77 °F)	100%
	0 °C (32 °F)	85%
	-15 °C (5 °F)	65%

Properties

Dimensions	15 cm x 6.5 cm x 9.4 cm (6 in. x 2.5 in. x 3.7 in.)
Total height with terminals	10 cm (4 in.)

Weight	2.5 kg (5.5 lb)
Terminal	Faston .187

Ordering information

D126 Standby Battery (12 V, 7 Ah)

A rechargeable sealed lead-acid power supply used as a secondary power supply or in auxiliary or ancillary functions.

Order number **D126**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia