



W-HN Series Wall-mount Horns



- ▶ **Sleek modern aesthetics**
- ▶ **Multiple voltages (12 VDC or 24 VDC)**
- ▶ **Voltage test points**
- ▶ **Three horn volume options**
- ▶ **Universal mounting base**
- ▶ **Environment-friendly low current draw**

The Cooper Wheelock Exceder Series Horns feature a sleek modern design that incorporates high reliability to minimize current draw. The reduced current draw allows for a greater number of devices on the two-wire notification appliance circuit. This, in combination with no tools needed for changing settings, voltage test points, 12 V or 24 V DC operation, the universal mounting base, and multiple mounting options results in a reduced cost of ownership.

These horns provide three sound settings on each appliance. All the switches to change these settings can be set without a tool and are located behind the appliance to prevent tampering.

The separate universal mounting base can be easily mounted to five industry-standard back box types. They can also be pre-wired to allow full testing of the circuit wiring before the appliance is installed and the surface finished. These wall-mounting horns also feature voltage test points for taking readings with a volt meter for troubleshooting or AHJ inspection.

Certifications and Approvals

Region	Certification	
USA	UL	ULSZ: Audible-signal Appliances (ANSI/UL 464)
	CSFM	7125-0785:168
Canada	ULC	ULSZC: Audible Signal Appliances and Accessories, Fire Alarm (CAN/ULC-S525, ULC-S527)

Cooper Wheelock has also designed these horn strobes to comply with:

US	FCC	Tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.
	NEC	National Electrical Code
	NFPA	NFPA 72

Installation/Configuration Notes

Compatibility

Horn:

These horns provide a selectable Continuous or Code 3 horn tone when connected directly to the Fire Alarm Control Panel (FACP). They can also provide a synchronized Code 3 Horn tone when used in conjunction with an FACP that incorporates the Cooper Notification sync protocol, a Cooper Notification Sync Module, or the Cooper Notification Power Supply. The Horn Appliances can be field set for High (HI), Medium (MED), or Low (LO) dBA sound output.

Compatible Products

The following Bosch Security Systems, Inc. products are compatible with the Cooper Wheelock Exceder Series Horns:

Category	Product ID	Product Description
Control Panels	FPA-1000-UL ¹	Compact Fire Panel
	FPD-7024 ¹	Conventional or Addressable ² FACP
	D10024A ³	Analog FACP
	D8024 ³	Analog FACP
	D9124 ³	Addressable FACP
	D7024 ³	Conventional or Addressable ² FACP
Modules	D7022 ³	Conventional FACP
	SM-12/24-R	Synchronization module (red)
Power Supplies	DSM-12/24-R	Dual synchronization module (red)
	FPP-RNAC-8A-4C ¹	Remote Notification Appliance Circuit (RNAC) Power Supply
	PS-24-8MC ¹	Power supply with built-in synchronization protocol

¹ These products have built-in Cooper Notification synch protocol.

² When used with a D7039 Multiplex Expansion Module, the FPD-7024 or the D7024 becomes an addressable FACP.

³ For synchronization, use the SM or DSM modules with these control panels.

Mounting Considerations

The Universal Mounting Base supplied with each horn can be pre-wired. With the supplied Contact Cover in place, the pre-wired circuit can be checked for continuity before the horns are mounted. The horns snap onto the pre-installed Universal Mounting Bases with the Contact Covers removed and can be secured to the base with an optional securing screw. The Universal Mounting Base flush mounts on single-gang, double-gang, 4 in. square, 4 in. octal, 3.5 in. octal, and 100 mm European-type back boxes.

Wiring Considerations

The wiring terminals on the Universal Mounting Base accept two appliance wires with diameters between 12 AWG (2.3 mm) and 18 AWG (1.2 mm) at each terminal.

Parts Included

Quant.	Component
1	Horn appliance
1	Universal mounting base
1	Contact cover
1	Hardware pack <ul style="list-style-type: none"> Two pan head mounting screws One securing screw
1	Literature – Installation Instructions

Technical Specifications

Audible Patterns and Ratings

Pattern	Volume Setting	Sound Output ¹		
		8.0 V	12.0 V	17.5 V
Continuous:	High:	83 dBa	88 dBa	91 dBa
	Medium:	79 dBa	82 dBa	86 dBa
	Low:	72 dBa	76 dBa	79 dBa
Code 3 ² :	High:	80 dBa	84 dBa	86 dBa
	Medium:	74 dBa	78 dBa	82 dBa
	Low:	68 dBa	72 dBa	76 dBa
		16.0 V	24.0 V	30.0 V
Continuous:	High:	91 dBa	93 dBa	96 dBa
	Medium:	86 dBa	89 dBa	92 dBa
	Low:	78 dBa	82 dBa	85 dBa
Code 3 ² :	High:	86 dBa	89 dBa	91 dBa
	Medium:	81 dBa	85 dBa	84 dBa
	Low:	74 dBa	78 dBa	80 dBa

¹ Sound output is a minimum UL rating based on sound power measurements at a distance of 10 ft (3 m) in a reverberant test room per UL464.

² The Code 3 temporal pattern (1/2 second on, 1/2 second off, 1/2 second on, 1/2 second off, 1/2 second on, 1-1/2 second off and repeat) is specified by ANSI and NFPA 72 for standard emergency evacuation signaling.

Note The Code 3 temporal pattern should be used only for fire evacuation signaling and not for any other purpose.

Environmental Considerations

Environment:	Indoor, dry
Relative Humidity:	93±2% maximum, non-condensing
Temperature (operating):	+32°F to +120°F (0°C to +49°C)

Mechanical Properties

Dimensions:	5.24 in. x 4.58 in. x 1.6 in. (133.1 mm x 116.4 mm x 40.7 mm)
Material:	Molded plastic enclosure
Volume Settings:	90 db, 95 db, or 99 db

Power Requirements

Horn Current Draw³

Voltage Type	Volume Setting	8.0 V to 17.5 V	16.0 V to 33.0 V
DC:	High:	47 mA	64 mA
	Medium:	26 mA	44 mA
	Low:	17 mA	22 ma
FWR:	High:	73 mA	86 mA
	Medium:	48 mA	74 mA
	Low:	36 mA	54 mA

Voltage (input)

Regulated	Range
12 VDC	8.0 V to 17.5 V
24 VDC or Vrms	16.0 V to 33.0 V

³ Current Draw is the same for the Continuous Horn and Code 3 Horn Settings.

Trademarks

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

Cooper Notification, Cooper Wheelock, Wheelock and Exceder are either trademarks or registered trademarks of Cooper Wheelock, Inc. which is a division of Cooper Menvier, a Cooper Industries, Ltd. company.

Ordering Information

W-HNR Wall-mount Horn (two-wire, 12/24 V, red) Rectangular red two-wire horn field-selectable for three volume options.	W-HNR
W-HNW Wall-mount Horn (two-wire, 12/24 V, white) Rectangular white two-wire horn field-selectable for three volume options.	W-HNW

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by