


HD-TVI Bullet Camera CMHR9323D




Key Features:

- HD 1080P Video Output
- Adopt HDTVI Technology
- True Day/Night
- Smart IR
- 131ft(40m) IR distance
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

Dimensions:





©2015 LT Security, Inc. | info@LTSecurityinc.com | www.LTSecurityinc.com





HD-TVI Bullet Camera CMHR9323D

CAMERA	
Image Sensor	1/2.9" CMOS
Signal System	NTSC/PAL
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Shutter Speed	1/30(1/25) s to 1/50,000 s
Lens	2.8-12mm
	Angle of View: 105.2° - 32.8°
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1080p@30fps/1080p@25fps
HD Video Output	1 Analog HD Output
S/N Ratio	More than 52dB
MENU	
AGC	Support
D/N Mode	Color/ BW/ Smart
White Balance	ATW/MWB
Language	English
Function	Digital noise reduction, Mirror
GENERAL	
Working Temperature	-40 ° F - 140 ° F (-40 ° C - 60 ° C)
/Humidity	Humidity 90% or less (non-condensing)
Power Supply	DC 12V, AC 24V
Power Consumption	Max. 6W
Weather Proof Ratings	IP66
IR Range	Up to 131ft(40m)
Dimension	4.1" x 3.4" x 11.9" (105.0× 86.9 × 302.3 mm)
Weight	3.3lb(1500g)

©2015 LT Security, Inc. All Rights Reserved. White papers, data sheets, quick start guides, and/or user manuals are for reference only and may or may not be entirely up to date or accurate based upon the version or models. Product names mentioned herein may be the unregistered and/or registered trademarks of their respective owners.