DATA SHEET

COD. 3340

DIGITAL CALL MODULE COMPLETE WITH ELECTRONIC NAME DIRECTORY

Complete with 128X64 dot graphic LCD display, keypad with 16 pushbuttons illuminated from the rear with blue LED's. Also operates as coded electronic key. It is complete with electronic name directory, which stores 400 user names. Name scrolling is carried out by using two search pushbuttons or by entering the initials of the name. Once the desired user name is displayed, simply press the call pushbutton. It is also possible to send the call by entering the user code directly. User programming is carried out in a simple way using programmer Art. 1230 or by means of the software for PC Art. 1249/A or 1249/B. Dimensions: 4.4?x7.1?x1.6?



Main specifications

Backlighting colour:	LED BLUE
Vandal Resistant IK:	No

Compatibility

Simplebus Top system:	Yes	
Simplebus Color system:	Yes	
Simplebus 2 system:	Yes	

Mounting/Installation

Flush-mounted:	Yes	
Wall-mounted:	Yes	
Surface-mounted:	Yes	

Audio/video specifications

Display size (inches):	3
Display resolution:	128x64 DOTS
Audio system:	Yes
Audio/video system:	Yes
Type of display:	LCD

Hardware specifications

Customisable housing:	No
DDE function:	No
Total buttons:	16
Sensitive Touch technology:	No

Software/firmware specifications

No. user codes:	1000
-----------------	------



DATA SHEET

1	No. of storable users:	1000
_		
Connectiv	vity	
_1	Type of connections/ports:	RS232, RS485, INFRARED
	nfrared port:	Yes
_F	RS232 ports:	1
<u>_</u> F	RS485 ports:	1
Functions	s - Settings	
ŀ	Key button function:	Yes
Technical	properties	
	Femperature range:	-25 / 55
Electrical	specifications	
	Maximum current absorption (mA):	100
General in	nfo	
	EAN product code:	'8023903118759
_	ntrastat code:	85176920
F	Product height (mm):	180
	Product width (mm):	112
F	Product depth (mm):	40
F	Product colour:	GREY
Packagin	g	
_	Single pack height (mm):	90
_	Single pack width (mm):	158
	Single pack weight (g):	590
	Single pack depth (mm):	160
-	Single pack volume (dm3):	2,275

