



MINI COLOUR MONITOR WITH HANDSET. BLACK. S2 SYSTEM





Wall-mounted monitor with 4.3" 16/9 colour screen and handset. Allows brightness and colour control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 8 soft touch buttons for door-opening, self-ignition, switchboard call and privacy service functions and with door status indicator LEDs. Manages floor door calls as standard. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

AWARDS









6701B		
MINI COLOUR MONITOR	WITH HANDSET. BLACK. S2 SYSTEM	
GENERAL DATA		
Product height (mm)	160	
Product width (mm)	175	
Product depth (mm)	22	
Product weight (g)	600	
Product color	Black RAL9005	
Material	ABS	
Wall-mounted	Yes	
COMPATIBLE SYSTEMS		
Audio/video Simplebus 2 with power supply art. 4888C	Yes	
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes	
Simplebus 2 audio/video kit with power supply art. 1209	Yes	
DISPLAY FEATURES		
Size (inches) (")	4.3	
Aspect Ratio	16:9	
Resolution (pixels)	480x272	
AUDIO FEATURES		
Microphone	6mm (Ø), Omnidirectional	
Loudspeaker	40 (ø) x 5.1 (H)mm, 100 ohm, 0.25W	
ELECTRICAL CHARACTERISTICS		
Type of power supply	Power supply from video door entry bus	
Supply voltage	22÷34 VDC (Bus)	
Maximum absorption (W)	5.4	

HARDWARE FEATURES





6701B	
MINI COLOUR MONITOR	WITH HANDSET. BLACK. S2 SYSTEM
Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Door open
No. of programmable buttons for additional functions	6
Clamps	L L CFP1 CFP2
Removable terminals	Yes
SETTINGS	
Ringtone volume	Yes
Screen brightness	Yes
Screen colour	Yes
ENVIRONMENTAL AND COMPLIA	NCE FEATURES
IP protection degree	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	I
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)
MAIN FUNCTIONS	
Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
CPS call	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes
Door opening on call (Doctor)	Yes
Door open signaling	Si

The technical specifications are subject to change without prior notice.

Yes

Yes

Call forwarding

Multiple address





MINI COLOUR MONITOR WITH HANDSET. BLACK. S2 SYSTEM

MAIN FUNCTIONS

Customisable ringtone	Yes
Sending alarm calls	Yes