



UT9270

TOUCH-SCREEN MODULE, ULTRA



Touchscreen module for Ultra entrance panel, compatible with all systems. Bluetooth connection for managing names in the directory using the installer's MyComelit app. Easy-to-use graphic interface allows the button interface to be customised for direct calls to switchboard, commercial activities (with corresponding logos), activation of an automated opening or light and viewing of apartment block messages. Can be used as a number keypad module to directly call the user when the relevant code is known, or for the access control function with activation of the audio or audio/video module outputs and the system actuators. 5" capacitive display with high visibility and impact-proof glass, plus theme selection (white or black). Has a Wiegand output for interfacing with access control systems. Equipped with RFID reader for activation of an opening using keys or Comelit cards. Automatic backlight regulation via the twilight sensor for the paired audio or audio/video module. Dimensions: 2 Ultra modules.

AWARDS



UT9270

TOUCH-SCREEN MODULE, ULTRA

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio/video Simplebus 1	Yes
Audio Simplebus 1	Yes
ViP	Yes

DISPLAY FEATURES

Display type	Graphic LCD
Size (inches) (")	5
Touch screen	Yes, capacitive
Resolution (pixel)	800x480

ELECTRICAL CHARACTERISTICS

Absorption in stand-by (mA)	2.85
Type of power supply	Power supply from video door entry bus
Maximum absorption (W)	3.3

HARDWARE FEATURES

Integrated proximity reader	RFID Mifare Classic
-----------------------------	---------------------

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating humidity (RH max - %) (%)	25 ÷ 95
Environmental class	IV

MAIN FUNCTIONS

Door opener	Yes
Access control via proximity reader	Yes



UT9270

TOUCH-SCREEN MODULE, ULTRA

MAIN FUNCTIONS

Access control via door opener code	Yes
Visual indications of system status	Yes
Customizable welcome message	Yes
Customizable screensaver	Yes

FEATURES

Backlight colour	White, Black
Call type	Digital
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Material	Polycarbonate
Product colour	Black RAL9005
Product depth (mm)	35
Product height (mm)	180
Product width (mm)	100
Type	Modular
Type of buttons	Capacitive

MAIN FEATURES

Operating temperature (°C)	-25 ÷ 55
Operating humidity (% RH max)	95
Supply voltage	33VDC
Clamps	GND D0 D1 IN D2- D2+ D1+ D1- GND

MOUNTING/INSTALLATION

Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory