



Summary

The VMAX[®] IP Plus[™] is an easy to use PoE NVR that allows you to go from power up to monitoring in less than three minutes! The NVR offers unique features such as CCIP[™] camera encryption and internal systems diagnostics, keeping your system healthy, secure and up to date. Combine with the DW Witness[™] app to turn the camera on a smartphone or tablet into a surveillance camera that can be viewed and recorded on the NVR.

Available with 4 PoE ports (expandable to 9 cameras), the NVRs can record and manage single-sensor IP cameras up to 5 Megapixel, with 80Mbps maximum throughput.

Features


- Simple and easy to navigate VMAX GUI for the most user-friendly solution on the market
- Complete installation, setup and camera configuration in under three minutes!
- Control any ONVIF camera's setup and features remotely
- DW Witness[™] turns a smartphone or tablet into an additional surveillance camera
- Pathfinder[™] auto port forwarding
- Record and manage single-sensor IP cameras up to 5MP (2592x1920), with 80Mbps maximum throughput (equivalent to 9 2.1MP IP cameras)
- Local power for up to 4 IP cameras via resident PoE switch
- CCIP[™] system encryption protects your surveillance system from out of network attacks
- Pivot[™] camera management software
- Mobile application for iPhone, iPad, iPod, Android smart phones and tablets and Apple TV
- Automatic device discovery
- Dual stream recording
- Easy drag and drop camera management
- Instant backup during playback
- Full HD (1080p) output for local live & playback display
- Complete system analysis with real-time system, network and PoE status monitoring
- True HD & VGA simultaneous output support
- 4 sensor input, 1 alarm relay output
- Up to 9ch transaction verification via TCP and USB-serial
- Email event notifications with video clip
- Simple & free DDNS support for remote management
- Easy web-based client with multi-user access
- Advanced H.264 linux embedded NVR
- Simultaneous live, playback, recording, back-up, network
- NVR health check with e-mail notification
- NVR calculation and auto recording configuration
- Help menu on major functions
- Auto or manual firmware upgrade available
- Automatic private IP addressing
- NTP (network time protocol)
- Screen saver to protect monitor screen
- Import/export configuration between multiple NVRs
- USB mouse and GUI control
- 5 year limited warranty

Available Models

- DW-VP92T4P – 2TB Internal Storage
- DW-VP94T4P – 4TB Internal Storage
- DW-VP93T4P – 3TB Internal Storage
- DW-VP96T4P – 6TB Internal Storage

Dimensions

Unit: Inch (mm)



Specifications



| | | |
|-------------------------------------|--|---|
| Operating System | | Embedded Linux [®] |
| System | Channel | 9 channel |
| | No. of PoE | 4 Ch |
| | Communication Protocol | ONVIF [®] |
| | PoE Type | 100Mbps, 802.3af |
| Display | Speed | 270fps |
| | Screen Mode | 1, 4 & 9 |
| Max. HDD Bay | 1 x SATA HDD | |
| Video-In | IP Camera (Max. 5MP (2592x1920)) | |
| Video-Out | Monitor | True HD and VGA |
| | Resolution | True HD Output: 800x600, 1024x768, 1280x1024, 1920x1080 |
| Recording Speed | FPS | 270fps |
| | Resolution | CIF, D1, 1.3MP, 2.1MP, 5MP |
| | Max. throughput | 80 Mbps |
| Recording Resolution | Dual Stream | |
| Recording Modes | Continuous, C+M, C+S, Scheduled, Sensor & Motion Detection Recording | |
| | Pre Alarm Recording, Emergency Recording, Quick Backup | |
| Playback & Search | Speed | x1, x2, x4, x8, x16, x32 |
| | Function | Intelli-Search by Time Bar, Calendar (Date & Time) and Event Search |
| Audio Output | 1 Ch | |
| Alarm Input / Relay Output | 4 Ch / 1 Ch | |
| PTZ Control | RS-485, ONVIF [®] | |
| Transaction Verification | TCP and USB-Serial Interface | |
| LAN | 1xGigabit Ethernet (RJ45) – Fixed IP, DHCP & DDNS | |
| Remote Software | Pivot Pro [™] , Web Client, Mobile Client for Android [®] & Apple [®] Smart Phones and Tablets and Apple TV | |
| Backup Device | Local Backup by USB, Network Backup by CMS | |
| System Recovery after Power Failure | Auto-Reboot and Journaling File System | |
| Other Function | Firmware Upgrade | FTP, USB |
| | Back Up | USB |
| | Special Features | Local PoE Switch |
| Health check | Real-Time System, Network and PoE Status Monitoring | |
| System Operation | IR Remote Controller (Optional), USB Mouse, PTZ Control by Keyboard (Optional) | |
| Power Requirements | 48V DC | |
| Power Consumption | 90.24W Total Power Budget, 1.88A, 15.4W per PoE Channel | |
| Operating Temperature and Humidity | 41~104 °F (5~40 °C) / 20~90% RH | |
| Dimension (WxDxH) | 10.39 x 9.65 x 1.73 Inch (264 x 245 x 44 mm) | |
| Certification | CE & FCC & KCC & WEEE, RoHS | |

