



**2.1** Megapixel Universal HD / Analog STAR-LIGHT™ Fixed Lens IP66 Rated **5YEAR** Warranty

## Summary

STAR-LIGHT™ 2.1MP Universal HD over COAX® cameras deliver crystal clear images and support real-time 30fps HD-Analog, HD-TVI, HD-CVI and all analog signals to 960H. The vandal dome cameras are IP67 rated and discrete in style. STAR-LIGHT™ Universal HD over COAX® cameras are engineered to work with our VMAX A1™ Universal HD over COAX® DVRs using your existing coax infrastructure for a cost-effective, high resolution surveillance solution.

## Features

- Universal HD over Coax® Technology with HD-Analog, HD-TVI, HD-CVI and all Analog to 960H Signal Support
- STAR-LIGHT™ Super Low Light Technology
- 2.1MP 1/2.7" Image Sensor at Real-time 30fps
- 3.6mm Fixed Lens
- Digital Wide Dynamic Range (D-WDR)
- OSD Control Via Coaxial (UTC)
- 50' Smart IR™ with Intelligent Camera Sync.
- Smart DNR™ 3D Digital Noise Reduction
- True Day/Night Mechanical IR Cut Filter
- De-Fog™ Extreme Weather Image Compensation
- Highlight Masking Exposure (HME)
- Programmable Privacy Zones
- Auto Gain Control (AGC)
- Backlight Compensation (BLC)
- Auto White Balance (AWB)
- IP66 Certified Weather and Tamper Resistant
- IK-10 Impact Rated
- 5 Year Warranty

## Accessories (Optional)



DWC-V7CM  
Pendant Mount for V7 Outdoor  
Dome Cameras



DWC-V7JUNC  
Junction Box for V7 Outdoor  
Dome Cameras




DWC-V7WM  
Wall Mount for V7 Outdoor  
Dome Cameras

## Dimensions

unit: Inch (mm)

UNIVERSAL  
HD COAX



## Specifications

IMAGE	
Image Sensor	2.1MP 1/2.7" CMOS Sensor
Active Pixels	1920(H) x 1080(V)
Scanning System	Progressive scan
Frequency	60Hz/50Hz
Video Output	HD-Analog, HD-TVI, HD-CVI 2.1MP 1080p CVBS Analog up to 960H
Synchronization	Internal
Resolution	1920x1080 (1080p)
Minimum Scene Illumination	F2.0 (30IRE): 0.41 Lux (Color) F2.0 (30IRE): 0 Lux (BW)
S/N Ratio	55dB
Signal Technology	Universal HD over Coax® Technology with HD-Analog, HD-TVI, HD-CVI and all Analog to 960H Signal Support
LENS	
Focal Length	3.6mm
Lens Type	Fixed Lens
IR Distance	50ft
OPERATIONAL	
Shutter Speed	1/30(25)-1/50,000
Backlight	Off/ On
STAR-LIGHT™ (Sense-up)	OFF, x2 -x30
Smart DNR™ 3D Digital Noise Reduction	Off, Low, Middle, High
White Balance	Auto / Auto-Ex/ Preset / Manual
Day and Night	Day/ Night/ Auto
Mirror/ Flip	Yes
Auto Gain Control	Max 50dB
Motion Detection	Yes
Privacy Zones	16 Privacy Zones
Sharpness	0 ~ 10
Gamma	0.45 ~ 0.75
ENVIRONMENTAL	
Operating Temperature	-4°F ~ 122°F ( -20°C ~ 50°C)
Operating Humidity	Less than 90% (Non-Condensing)
IP Rating	IP66 Certified Weather and Tamper Resistant
IK Rating	IK10-Rated Impact Resistant
Other Certifications	FCC, CE, ROHS
ELECTRICAL	
Power Requirements	DC 12V
Power Consumption	DC12V (LED OFF): 1.92W DC12V (LED ON): 3.12W
MECHANICAL	
Material	Aluminum
Dimensions	4.13 x 2.39 Inch (105 x 60.7 mm)
Weight	0.95 lbs (430.9 gr)