

D200 Series

200kA / Ø, 100kA / Mode - Surge Protective Device



Product Features

- 200,000 Amps/phase surge current rating ensures long service life
- Compact size enables close mounting to the protected panel, to minimize wire length and maximize performance
- Diagnostic LED indicates system power, SPD function, alarm and ground status
- Dry Contacts for remote monitoring
- Available in 8 voltage configurations

Applications

- Service Entrance
- Branch Panel

Accessories

- Flush Mount Kit: D200-FMK

DITEK's D200 Industrial Surge Protectors are designed to provide protection to AC power systems in the most demanding environments. The D200 Series incorporates individually fused components for maximum performance and protection. Available in a wide range of voltage configurations, the compact D200 is an excellent choice for electrical panel protection.

Technical Specifications

Service Voltage:	Single, split & three phase configurations. See chart
Surge Current Rating:	200,000 Amps per phase, 100,000 Amps per mode
SCCR:	100,000A
Operating Frequency:	40Hz – 400Hz

Mechanical Characteristics

Connection Method:	¾" NPT conduit, watertight fittings
Housing:	NEMA 4X
Operating Temperature:	-40°F - 140°F (-40°C - 60°C)
Maximum Humidity:	95% non-condensing
Dimensions:	6.3"Lx 2.4"W x 6.3"H (160mm x 61mm x 160mm)
Weight:	2.9 lb. (1.3kg)

Quality, Standards & Approval

Agency Approvals:	UL1449 Listed, cUL
SPD Type:	SPD Type 1 (US), SPD Type 2 (Canada)
Standards Compliance:	ANSI/IEEE C62.41 and C62.45 Category B and C3
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.



D200 Series

200kA / Ø, 100kA / Mode - Surge Protective Device



Part Number	Service Voltage	Service Configuration	MCOV	UL I _n Rating	Voltage Protection Rating (VPR)			
					L-G	L-L	L-N	N-G
D200-120/2401	120VAC	Split Ø (3W + G)	150V/300V	20kA	600V	1000V	600V	900V
D200-120/2083Y D200-127/2203Y	120/208VAC	Three Ø Wye (4W + G)	150V/300V	20kA	600V	1000V	600V	900V
D200-120/240HL	120/240VAC	Three Ø High Leg Delta (4W + G)	150V/320V	20kA	600V HL-G 1200V	1000V HL-L 1500V	600V/ HL-N 1000V	900V
D200-277/4803Y D200-220/3803Y D200-230/4003Y D200-240/4153Y	277/480VAC	Three Ø Wye (4W + G)	320V/640V	20kA	1200V	1800V	1000V	1800V
D200-347/6003Y	347/600VAC	Three Ø Wye (4W + G)	420V/840V	20Ka	1500V	2500V	1500V	2500V
D200-2403D	240VAC	Three Ø Delta (3W + G)	320V/640V	20kA	1200V	1800V	N/A	N/A
D200-4803D	480VAC	Three Ø Delta (3W + G)	550V/1100V	20kA	1800V	3000V	N/A	N/A
D200-6003D	600VAC	Three Ø Delta (3W + G)	840V/1680V	20kA	3000V	6000V	N/A	N/A

