



DTK-8FF

8-Outlet Plug-In Surge Protection General Product Specifications

DITEK's DTK-8FF eight outlet SPD (Surge Protective Device) protects AC power and telco/modem/fax lines. Hybrid circuitry provides excellent point of use protection. Up to six transformers can be used at the same time. EMI/RFI filtering provides extra protection for sensitive electronics.



DTK-8FF

Product Features

- 8AC outlets protected, up to six transformers
- Diagnostic LED indicates ground presence and suppressor function
- Automatic shutdown feature turns off power in case of suppressor overload
- 1 in / 2 out RJ11 Telco protection included
- Mounting slots allow installation on wall or backboard
- Six foot cord
- Ten year limited warranty

Specifications

Agency Approvals:	UL1449, 3 rd Edition (AC) UL497A (Telco) SPD Type 3
Service Voltage:	110-120VAC
MCOV:	125VAC, 130V Telco
Connection:	Direct plug-in (AC); RJ11 (Telco)
Continuous Current:	15 Amps
Max Surge Current:	144,000 Amps Total (AC) 5,000 Amps (Telco)
Nominal Discharge Current:	3,000 Amps
Joule Rating:	2,160j (AC); 160j (Telco)
Protection Modes:	L-G, L-N, N-G (AC) Tip-G, Tip-Ring, Ring-G (Telco)
U.L. Voltage	
Protection Rating:	330V L-N, 400V L-G, N-G
Dimensions:	10.5" x 3.9" x 1.4" (267mm x 99mm x 36mm)
Weight:	1.3lb (590g)
Housing:	ABS

