



DTK-SL "Snap-Lite" Series

66 Block Quick-Connect Surge Protection General Product Specifications

The DITEK Snap-Lite quick-connect line protector is designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage. Available in four different voltages, there is a Snap-Lite for virtually any analog 66 block application.



DTK-SL Series

Application Features

- Quick connect module – no bridge clips required!
- Each Snap-Lite protects one pair
- Field-replaceable
- Self-resetting fusing
- Models available for both current-limited and standard lines

Product Features

Agency Approvals: UL497A, UL497B

Connection Method: Stab connection to 66 Block

Max Continuous Current: 150mA (-A models),
2A (-B models)

Max Surge Current: 1,000 Amps per pair (30V)
5,000 Amps per pair (50V)
4,000 Amps per pair (75V-130V)

Protection Modes: Tip-Ground, Ring-Ground

Operating Temperature: -40°F - 158°F (-40°C - 70°C)

Maximum Humidity: 95% non-condensing

Dimensions: 1.56"H x 3.24"W x .38"D
(39.6mm x 82.3mm x 9.6mm)

Weight: .5oz (14g)

Housing: High Impact Plastic

Warranty: Ten Year Limited Warranty

Accessories: Ground Bus – part number DTK-SIGB

NOTE: Each 66 Block requires one 'SIGB' ground bar

Selection Guide

DTK-SL##A (150mA current); **DTK-SL##B** (2A current)
The "A" suffix denotes UL497A Listed
The "B" suffix denotes UL497B Listed

- Service Voltage: 30V, 50V, 95V, 130V

Example: DTK-SL30A

Example: DTK-SL130B

Performance Data

Model DTK-SL##	Service Voltage	MCOV	Clamp Voltage
30	30V	38VDC	47V
50	50V	66VDC	82V
95	95V	127VDC	150V
130	130V	175VDC	204V

