



DTK-UPS+ Series On-Line Uninterruptible Power Supplies



DITEK's DTK-UPS+ Series is designed with the latest online double conversion Uninterruptible Power Supply technology to enable your equipment to survive even the harshest power quality issues. From surges and spikes to brownouts and complete power loss, the DTK-UPS+ Series will keep your equipment up and running when it matters most. DITEK's industry proven UPS products provide cost-effective and reliable performance for network servers, video surveillance systems, back office computers and similar mission critical equipment.

Product Features

- Online double conversion technology provides superior equipment protection
- 1000VA – 3000VA models available
- Compliant to U.S. DOE Energy Conservation Standard efficiency requirements (January 2022)
- Programmable power management outlets
- Hot swappable battery design
- Easily converts from rack mount to tower profile
- Invisible transitioning between AC and battery
- Intuitive LCD display
- USB and Ethernet interfaces available on all models
- Software provided for remote monitoring
- Supports auto shutdown when battery is depleted
- Compatible with backup generator systems

Applications

- Network Servers
- Video Surveillance Systems
- Back Office Computers
- PC-Based Phone Systems
- Point of Sale Devices

Accessories

- SNMP Card, p/n DTK-UETH1
- Mounting Rails (included with 1.5kVA, 2kVA and 3kVA models), p/n DTK-URK1
- Replacement Battery, p/n DTK-UB12460

Extended Battery Pack Model Numbers

- DTK-UXB1000R+ for DTK-UPS1000R+
- DTK-UXB1500R+ for DTK-UPS1500R+
- DTK-UXB2000R+ for DTK-UPS2000R+
- DTK-UXB3000R+ for DTK-UPS3000R+





DTK-UPS+ Series On-Line Uninterruptible Power Supplies

Technical Specifications				
Part Number:	DTK-UPS1000R+	DTK-UPS1500R+	DTK-UPS2000R+	DTK-UPS3000R+
Capacity:	1000VA, 1000W	1500VA, 1500W	2000VA, 2000W	3000VA, 3000W
INPUT – Voltage Rating and Required Power				
Voltage Rating:	100/110/115/120/127VAC			
Required Power Outlet:	NEMA 5-15R (15A)	NEMA 5-15R (15A)	NEMA 5-20R (20A)	NEMA L5-30R (30A)
Low Line Transfer:	80VAC / 70VAC / 60VAC / 55VAC ± 5% (Based on load percentage 100% - 80% / 80% - 70% / 70% - 60% / 60% - 0)			
Low Line Comeback:	87VAC / 77VAC / 67VAC / 62VAC ± 5%			
High Line Transfer:	150VAC ± 5%			
High Line Comeback:	144VAC ± 5%			
Frequency Range:	40Hz - 70Hz			
Power Factor:	≥ 0.99 @ Nominal Voltage (100% load)			
OUTPUT				
Output Voltage:	100/110/115/120/125/127VAC			
AC Voltage Regulation:	± 1% (Battery mode)			
Frequency Range:	47 ~ 53Hz or 57 ~ 63Hz (Synchronized range) / 50Hz ± 0.1Hz or 60Hz ± 0.1Hz (Battery mode)			
Current Crest Ratio (CF):	3:1			
Harmonic Distortion:	≤ 2% THD (Linear load), ≤ 4% THD (Non-linear load)			
Transfer Time:	AC Mode to Battery Mode: Zero Inverter to Bypass: < 4 ms			
Waveform (Battery Mode):	Pure Sine wave			
OUTLETS				
Programmable (non-critical loads):	4 @ 15A	4 @ 15A	4 @ 15A/20A	3 @ 15A/20A
Receptacles (mission-critical loads):	4 @ 15A	4 @ 15A	4 @ 15A/20A	3 @ 15A/20A, 1 @ 30A
EFFICIENCY				
AC Mode:	≥89% @ Full Charge		≥90% @ Full Charge	
ECO Mode:	≥96% @ Full Charge			
Battery Mode:	≥88%		≥90%	
BATTERY				
Battery Type – Quantity:	12V/9Ah - 2	12V/9Ah - 3	12V/9Ah - 4	12V/9Ah - 6
Typical Recharge Time:	3 hours to recover to 95% capacity			
Battery Runtime (100% Load):	2 min, 45 sec	2 min, 55 sec	2 min, 45 sec	2 min, 56 sec
(50% Load):	9 min, 30 sec	9 min, 33 sec	9 min, 40 sec	9 min, 50 sec
INDICATORS				
LCD:	UPS Status, Load Level, Battery Level/Info, Input/Output Info, Discharge Time, Fault Indicators			
Alarm Sounding:	BATTERY MODE: every 5 seconds - LOW BATTERY: every 2 seconds OVERLOAD: every second - FAULT: continuously sounding - BYPASS: every 10 seconds			
PHYSICAL & ENVIRONMENTAL				
Dimensions (L x W x H)	16.14" x 17.24" x 3.46"	20.0" x 17.24" x 3.46"	20.1" x 17.24" x 3.46"	24.8" x 17.24" x 3.46"
Weight	25.57 lbs	34.17 lbs	43.00 lbs	60.63 lbs
Humidity:	20 – 95% RH @ 0 - 40°C (non-condensing)			
Noise Level:	< 50dBA @ 1 Meter (With fan speed control)			
MANAGEMENT				
Smart RS-232/USB:	Compatible with Windows 2000/2003/XP/Vista/2008/7/10, Linux, Unix, MAC			
Optional SNMP:	Power management from SNMP manager and web browser			
QUALITY STANDARDS & APPROVALS				
Certifications:	cTUVus (compliant to UL1778) U.S. DOE Energy Conservation Standard (01/2022)			
Warranty:	3 Year Limited Warranty			

Derate capacity to 95% when output is adjusted to 115VAC, to 90% when adjusted to 110vac, and to 80% when adjusted to 100VAC