



1834 90 SERIES TELEPHONE ENTRY SYSTEM



Best Suited for Applications Requiring Control of a Single Door or Gate and in Applications where Card Readers or other Expansion Options are not Required

- Provides both resident and visitor Access Control into apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites.
- Built-In Electronic Directory
- Large, Easy-to-Use A-Z-CALL Buttons
- PC Programmable – Programming and Transaction Analysis Software Available for Download at doorking.com/software
- Voice and Data Programming Connection via Cellular, Internet, or Copper POTS Lines
- 2-Year Limited Factory Warranty

Shown with 10 Gauge Stainless Steel Hood sold separately



Voice and Remote Programming
use DKS service options for connection and programming


One Box That Mounts Anywhere



Optional
internal TCP / IP for internet connection



Internal LED
lit keypad and A-Z-CALL buttons



PC Programmable
easy-to-use software available for download at doorking.com/software



Surface


Flush

Post

shown with trim ring sold separately




1834 90 SERIES TELEPHONE ENTRY SYSTEM




1834 90 SERIES

12.75" W x 14.75" H x 3.75" D
(323.85 mm W x 374.65 mm H x 95.25 mm D)

OPTIONAL MOUNTING ACCESSORIES



1814-185 Black Hood
1814-180 Stainless Steel Hood
13.08" W x 14.88" H x 5.61" D
(332.00 mm W x 378.00 mm H x 142.50 mm D)



1814-200 Stainless Steel Flush Mount Kit
15.34" W x 17.27" H x 3.76" D
(389.63 mm W x 438.65 mm H x 95.25 mm D)

1834 90 SERIES

PHONE # MEMORY	3000 Phone Numbers, 255 Area Codes
ENTRY CODES	3000 (4-digit)
DEVICE CODES	0
DOOR CONTROL	2 Entry Points
DIRECTORY	Single-Line 20-Character Super-Twist LCD Display (1/2 inch characters)
ELEVATOR CONTROL	No
PROGRAMMING	PC with Remote Account Manager Software*
TRANSACTION BUFFER	8000 Events

* DKS Remote Account Manager Software is available as a free download at doorking.com/software

TECHNICAL FEATURES

MECHANICAL

- Stainless Steel Faceplate
- Galvanized Steel Sub-Plate
- Metal Internally-Lit LED Keypad and A-Z-CALL Buttons
- Offset Speaker Holes for Protection
- Built-In Postal Lock Provision
- Flush Mount Requires Flush Mounting Kit
- Stainless Steel & Black 10 Gauge Hood Available
- Enclosures are Rated NEMA 4x
- Internal provision for TCP/IP adapter (1830-185, 1830-186 only)
- Space for optional LCD heater

CONNECTION METHODS

- Cellular *powered by AT&T 4G LTE*
 - Internet *select DK VoIP or your own VoIP provider*
 - POTS *Plain Old Telephone Service*
- Some of the connection methods noted may incur additional cost for required hardware and/or service subscriptions.

SPECIFICATIONS

- 16 VAC (2 Power Transformers included)
- Full Duplex Hands-Free Voice Communication
- Programmable Directory Codes (1 to 4 digits)
- 10 & 11-Digit Dialing Capability
- Built-in Clock / Calendar
- Live Transactions Feature (requires TCP / IP internet connection or RS-232 connection)

MISCELLANEOUS

- Environmental: 10° F to 145° F (-12° C to 62° C)
- Heater Kit (P/N 2600-584) Recommended when Temperatures Routinely Fall Below 35° F (1.6° C)
- Optional High-Resolution Camera Kits *additional CCV equipment and cabling required*
- Shipping Weight Approximately 15-20 lb (6.8-9 kg)

FCC (US) DUF6VT-12874-OT-T
DOC (CAN) 1736 4528 A

Conforms To UL STD 294
Certified To CSA STD 22.2 #205
Intertek

AT&T, the AT&T logo and all other AT&T marks contained herein are trademarks of AT&T Intellectual Property and/or AT&T affiliated companies.

DoorKing®, Inc.

Access Control Solutions since 1948



120 S. Glasgow Avenue,
Inglewood, California 90301 U.S.A.
Tel: 310-645-0023 FAX: 310-641-1586
www.doorking.com

© 2018 All Rights Reserved.
Product specifications may
change without notice. Rev. 11/18

MEMBER:



DISTRIBUTED BY:

