



PGx901 Wireless PowerG Indoor Siren

- Visible link quality indicator on device
- 110db siren with strobe light
- Differentiated audible alerts for intrusion and fire
- Prolonged battery life (8 years with typical use)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.44 x 1.75in)

Available in NA, LATAM, Europe, Africa and APAC



PGx911 Wireless PowerG Outdoor Siren

- 110db siren output
- Strobe light functionality for visual indication
- Sleek design and robust weatherproof housing (IP55)
- Fully supervised
- Prolonged battery life (8 years with typical use)
- Differentiated alarm sounds for intrusion, fire, gas and flood
- Large print screen area for customizable logos
- Dimensions: 295 x 186 x 63mm (11.63 x 7.31 x 2.5in)
- Available with Amber strobe, depending on country

Available in NA, LATAM, Europe, Africa and APAC



PGx920 Wireless PowerG Repeater

- Extends the overall wireless range
- LED indications for power failure, activity and installation performance diagnostics
- Compact and easy to install
- Front and back tamper protected
- Replacement Battery BATT1.3-4.8V
- Mains powered with 48 hour backup battery (rechargeable)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.445 x 1.74in)

Available in NA, LATAM, Europe, Africa and APAC

Intrusion Detectors



 WS4904P Wireless Pet-Immune PIR Detector	 WS4945 Wireless Door/Window Contact	 EV-DW4927SS Wireless Shock Sensor with Built-In Door/Window Contact	 EV-DW4975 / EV-DW8975 Wireless Vanishing Contact	 EV-DW4917 Wireless Recessed Door Transmitter	 AC-100 / AC-500 Wired Glassbreak Detector	 BV-500 Wired 360° Ceiling-Mount PIR Motion Detector
 LC-100-PI Wired PIR Detector with Pet-Immunity	 BV-300 Wired PIR Detector	 LC-151/171 Wired Pet-Immune Dual-Tech Outdoor Motion Detectors	 SS-102 Wired Shock Sensor	 BV-600 Wired Dual-Element, Pet-Immune PIR Motion Detector	 LC-103-PIMSK / LC-104-PIMW Wired Dual-Tech Motion Detector with Pet-Immunity	 AMB-500 Addressable Ceiling-Mount PIR Detector
 AMB-300 Addressable PIR Detector	 AMB-600 Addressable Pet-Immune PIR Detector	 AMP-700 / AMP-701 AMP-702 / AMP-704 Addressable Contact Modules				




Safety Sensors

 WS4936 Wireless Photoelectric Smoke Detector	 WS4913 Wireless Carbon Monoxide Detector	 WS4985 Wireless Flood Detector	 FSA-210/410 Wired Photoelectric Smoke Detector	 FSB-210 Series Addressable Photoelectric Smoke Detector
---	---	---------------------------------------	---	--

Control Panels

 PC1864 8-64 Zone Control Panel	 PC1832 8-32 Zone Control Panel	 PC1616 6-16 Zone Control Panel
---------------------------------------	---------------------------------------	---------------------------------------



Keypads, Arming Devices & Panic Buttons

 PK5500 64-Zone LCD Full-Message Keypad	 PK5501 64-Zone LCD Picture Icon Keypad	 PK5508 8-Zone LED Keypad	 PK5516 16-Zone LED Keypad	 PTK5507W TouchScreen Security Interface	 PTK5507S TouchScreen Security Interface	 WT5500-WT5500P 2-Way Wire Free Keypad (optional Proximity tag support)	 WTK5504 / WTK5504P Wireless TouchScreen Arming Station
 WS4949 2-Button Wireless Key	 WS4959 5-Button Wireless Key	 WT4989 2-Way Wireless Key	 WS4938 1-Button Wireless Personal Panic	 WS4939 4-Button Wireless Key	 RFK5500 64-Zone LCD Full-Message Keypad with Built-In Wireless Receiver, 32 wireless zones	 RFK5564 64-Zone Full-Message Keypad with Built-In Wireless Receiver (up to 64 wireless zones)	 RFK5501 64-Zone LCD Picture Icon Keypad with Built-In Wireless Receiver, 32 wireless zones



Repeaters, Receivers, Modules and Communicators

 WS4920 Wireless Repeater	 RF5132-433 Wireless Receiver	 PC5320 Multiple Wireless Receiver Module	 TR5164-433 2-Way Wireless Transceiver	 PC5108 8-Zone Hardware Expander	 PC5100 Addressable Zone Expander	 IT-230 RS-422 Interface Module	 IT-100 Serial Integration Module
 PC5200 / PC5204 Power Supply Modules	 PC5208 Programmable Output Module	 3G2060R HSPA Cellular Alarm Communicator	 TL260R Internet Alarm Communicator	 TL2603GR Internet & HSPA Dual-Path Alarm Communicator			



PC5320 Multiple Wireless Receiver Module

- Multi-frequency support for combination of 900/433 MHz receivers
- Compatible with PC1616, PC1832 and PC1864 PowerSeries control panels
- Can be used to connect up to 4 wireless receivers for increased coverage

Available in NA, LATAM, EMEA and APAC



PC5100 PowerSeries Addressable Zone Expander

- Connect up to 32 addressable detectors (AML)
- Detectors can be home-run, t-tapped or daisy chained
- Easy detector enrollment process
- Compatible with PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC



PC5108 PowerSeries 8-Hardwire Zone Expander

- Adds 8 hardwire zones
- AUX power, 125 mA (PTC protected)
- Compatible with PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC



PC5200 / PC5204 PowerSeries Power Supply Modules

- Fully supervised for AC failure, low battery and AUX failure
- PC5204 adds 4 programmable high current voltage outputs: rated at 1 Amp @ 12 VDC, output #1 can be used as a supervised bell output
- Connect one PC5204 and up to four PC5200 supervised modules on a system
- Provides up to 1 Amp @ 12 VDC
- Compatible with PC1404, PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC



PC5208 PowerSeries Programmable Output Module

- Provides 8 low current (50 mA) PGM voltage outputs
- Compatible with PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC

PC5400 Printer Interface Module

- Compatible with PC1616, PC1832 and PC1864 control panels
- Can be used to support a serial printer

Available in NA, LATAM, EMEA and APAC



PC5950 Universal 2-Way Vox Audio Verification Module

- Supports both 2-way audio VOX and push-to-talk verification
- Supports 4 microphones and 2 speakers
- KEYBUS direct connect allows all programming to be performed at the system keypad or remotely using dls 5 software
- KEYBUS compatible with PC1616, PC1832 and PC1864 control panels
- Universal installation compatibility with any control panel using either PGM and/or Bell dry contact outputs
- Silent/Listen-in functionality on hold-up alarms (activates only when an alarm occurs)
- User call-in feature

Available in NA, LATAM, EMEA and APAC



IT-230 RS-422 Interface Module

- Compatible with PowerSeries panels v4.5 and higher
- 4-wire keybus and included PC-LINK header hookup
- Compatible with leading-edge interactive solutions supported by DSC

Available in NA



IT-100 PowerSeries Integration Module

- Bi-directional RS-232 interface
- Real-time zone status
- Fully programmable
- 4-wire hook-up to KEYBUS
- Virtual keypad mode
- Compatible with PowerSeries control panels PC1616/PC1832/PC1864
- Thermostat control functionality via a DSC Escort module

Available in NA, LATAM, EMEA and APAC

