# **Delayed Egress Systems**





# 3101C Series 1500 Lb. Delay Egress System

Delay egress electromagnetic locks, surface mounted for outswing single or double doors and inswing single doors. Non-handed.

Sizes: 3"D x 2-3/4"H x 11"L (3101C) 3"D x 2-3/4"H x 22"L (3121C) 3"D x 2-3/4"H x 11"L ea. (3121C2) 2-3/4"D x 4"H x 11"L (3101C-TJ101)

Multi-voltage field selectable 12/24 VAC/VDC

Current Draw: 460 mA @ 12VDC / 260 mA @ 24VDC (3101C, 3101C-TJ101)

840 mA @ 12VDC / 470 mA @ 24VDC (3121C, 3121C2)



| MODEL       | PRODUCT                                      | FINISH | WEIGHT  |
|-------------|--|--------|---------|
| 3101C       | Single Delay Egress Lock Outswing            | US28   | 12 Lbs. |
| 3121C       | Double Delay Egress Lock Pair Outswing       | US28   | 24 Lbs. |
| 3121C2      | Double Delay Egress Lock Pair Outswing       | US28   | 24 Lbs. |
|             | Tandem Unit To Accommodate Center Mullion    |        |         |
| 3101C-TJ101 | Single-Inswing Delay Egress Lock Kit         | US28   | 15 Lbs. |
|             | Includes "Z" Bracket, Shim Plate, Door Sign, |        |         |
|             | Wall-Mount Keyswitch (#7050-LED)             |        |         |



#### **OPTIONS**

| ATS   | Anti-Tamper Switch - Signals removal of the housing cover. |
|-------|--|
| ATS2  | Anti-Tamper Switch - For the 3121C and 3121C2              |
| • BPM | Bypass Monitor - Signals bypass keyswitch activation       |
| DSM   | Door Status Switch - Signals door closed or ajar.          |
| DSM2  | Door Status Switch - For the 3121C and 3121C2.             |
| DYN   | Dynastat Force Sensor - Indicates efficient magnetic bond. |
| DYN2  | Dynastat Force Sensor - For the 3121C and 3121C2.          |
| ETR   | Egress Sensor Omitted - For externally triggered egress.   |
| KSO   | Keyswitch Omitted - In favor of separate remote keyswitch. |
|       | (Suggested for door heights over 8 ft.) See page 47.       |
| * LP  | Low Power Coil - 12V only @ 0.40 Amps (Single Lock)        |
| LP2   | Low Power Coils - 12V only @ 0.72 Amps (Double lock)       |
| SF    | Special Finish - Standard finish US28. Special anodized    |
|       |  |



3101C-TJ101

## BUILDING CODE SOFTWARE OPTIONS (FACTORY INSTALLED)

| BOCA | For operation in compliance with BOCA Code.             |
|------|---|
| UBC  | For operation in compliance with UBC Code.              |
| CHGO | For operation in compliance with Chicago Building Code. |

Notes: • BPM option not available with the KSO option.

finishes see page 56.

\* LP option may not be combined with DYN option.

## **REPLACEMENT ITEMS & LEGACY PRODUCTS**

| SIGN 15     | Door sign only, 15 second delay verbiage.               |
|-------------|---|
| SIGN 30     | Door sign only, 30 second delay verbiage.               |
| 3101B       | Single Delay Egress Lock Outswing (Legacy Product)      |
| 3121B       | Double Delay Egress Lock Pair Outswing (Legacy Product) |
| 3121B2      | Double Delay Egress Lock Pair Outswing (Legacy Product) |
| 301424      | "PULL" Door Sign, 3101C/3101B-TJ101                     |
| 3101B-TJ101 | Single-Inswing Delay Egress Lock (Legacy Product)       |

2016 Catalog, First Edition Tel: 1.877.DYNALOCK Page 26 Fax: 1.860.585.0338 ©2016 DynaLock Corp.