



# Eagle Eye Cloud VMS

## WHAT IS THE EAGLE EYE CLOUD VMS?

The Eagle Eye Security Camera VMS is a fully managed cloud video surveillance solution, delivering an end-to-end video management system that's simple to deploy and easy to use. It supports all modern browsers and works on Windows, Mac, even Linux with no plugins to install.

## FULLY MOBILE

View video anytime, anywhere. The fully functional iOS and Android applications provide complete access to live and recorded video and can also be used to install, configure and manage the system.



## GOT CLOUD?

Eagle Eye Networks provides a cloud based, video management system. The Eagle Eye Bridge is installed on-site, connects to your cameras, records video locally, and then securely synchronizes both video and meta data to the Eagle Eye Cloud Data center. It's a robust, secure appliance specifically designed to overcome the demands of transmitting high-resolution video through the Internet.

## COMPREHENSIVE CAMERA SUPPORT

At Eagle Eye Networks we believe camera compatibility is important. There's no need to be locked into a single camera vendor. Businesses need the flexibility to work with the cameras that they choose. Eagle Eye Bridges and CMVRs support ONVIF Profile S IP cameras. Eagle Eye Combo Bridges and CMVRs support IP as well as NTSC and PAL analog cameras. For an up to date list of all compatible cameras visit [www.een.com/cameras](http://www.een.com/cameras).

## WORRY FREE MANAGEMENT

All of the software in the Eagle Eye Cloud and firmware on the Eagle Eye Bridge is managed and updated by Eagle Eye Networks. The hardware is fully backed by Eagle Eye with full replacement if anything ever goes wrong.

## SECURITY SIMPLIFIED

With Eagle Eye Complete Privacy Encryption™, video is fully encrypted during transmission and at rest. The Eagle Eye Bridge has no open ports to the Internet, eliminating security vulnerabilities commonly found in other systems and requiring no router or firewall adjustments.

# Eagle Eye

# Compact Bridge

# 304

# 304w

# 305

# 306



The Eagle Eye Bridge acts as a gateway from your premises to the Eagle Eye Cloud Data Center where your video is stored and managed by the Eagle Eye Cloud VMS. It provides video buffering, a secure connection, bandwidth management, and monitoring of cameras.

These small form factor bridges are suitable for applications up to 25 cameras when a server rack is not available. They are suitable for wall or shelf mounting. The Bridge 304w is designed to support WiFi cameras. The Bridge 305 is a ruggedized, all aluminum version with a broader industrial temperature range and includes 4 POE ports for direct camera connection. It's sometimes used in vehicle applications. The Bridge 306 provides support for the largest number of cameras.

## RECORDING FEATURES


- Video encrypted in transit and at rest
- Fully cloud managed
- Intelligent Bandwidth Management with local buffering
- Motion or continuous recording
- Optional audio recording

## WEB INTERFACE & MOBILE FEATURES

- Native iOS and Android apps
- View live and recorded video
- Compatible with all modern browsers
- Motion detection with alerts
- Map and floorplan display

## SYSTEM ADMINISTRATION

- 100% browser-based; no software
- Granular user permissions
- Multi-site support
- Point and click video sharing
- Centralized management



## NETWORK FEATURES

- Automatic network configuration
- Secure camera network (dual network ports)
- No inbound connections needed
- Packet loss detection/reporting
- Network disconnected alerts

## MANAGEMENT FEATURES

- Remote management
- Automatic camera discovery
- Automatic camera configuration
- Advanced motion detection
- Local video buffering
- Configuration synced to Cloud
- Camera trouble alerts
- Internet outage alerts
- Fully cloud managed

### STANDARD SUPPORT (Included)

- Free of charge with an active subscription
- Replacement of Bridge at no cost
- 24/7 email and web support
- 8 am to 6 pm phone support



### RAPID REPLACEMENT (Recommended)

Eagle Eye's comprehensive program for hardware warranty and upgrades.

- Extends warranty up to 20 years
- 24/7 priority support via phone, email and web
- Overnight cross shipping of warranty replacement if needed
- Full equipment upgrade every 6 years up on request

MODEL	Bridge 304	Bridge 304w	Bridge 305	Bridge 306
Max Cameras (1MP)*	15 IP	15 IP, 4 WiFi	15 IP	25 IP
Max Cameras (4MP)*	12 IP	12 IP	12 IP	16 IP
Max Analytic Count*	5	5	5	10
Video Buffer	2 days on-premise	2 days on-premise	2 days on-premise	2 days on-premise
POE Camera Ports	None	None	4 port, Class 3	None
Network Ports	Dual Gigabit	Dual Gigabit	Dual Gigabit	Dual Gigabit
Video Output	HDMI (1), DP (1)	HDMI (1), DP (1)	HDMI (1), DP (1)	HDMI (1), DP (1)
Dimension	125 x 127 x 50 mm 5.00 x 5.01 x 1.75 in	125 x 127 x 50 mm 5.00 x 5.01 x 1.75 in	172 x 127 x 75 mm 6.75 x 5.01 x 3.00 in	127 x 125 x 52 mm 5.01 x 5.00 x 2.26 in
Power	External 100-240 VAC, 20 W	External 100-240 VAC, 20 W	External 100-240 VAC, 22 W	External 100-240 VAC, 20 W
Operating Temperature Range	0-35° C 32-95° F	0-35° C 32-95° F	-10-50° C 14-122° F	0-40° C 32-104° F
Operating Humidity Range	0-70%	0-70%	0-70%	0-70%
Certifications	FCC, UL, PSE, CE, CCC(S&E), REACH, RoHS, C-Tick, NDAA	FCC, UL, PSE, CE, CCC(S&E), REACH, RoHS, C-Tick, NDAA	FCC, UL, PSE, CE, CB, TIS, NDAA	FCC, CE, ICEC, NDAA
Rapid Replacement Part Numbers	EN-RR304-1 (Monthly) EN-RR304-12 (Yearly)	EN-RR304w-1 (Monthly) EN-RR304w-12 (Yearly)	EN-RR305-1 (Monthly) EN-RR305-12 (Yearly)	EN-RR306-1 (Monthly) EN-RR306-12 (Yearly)

\* Typical - please utilize the Eagle Eye VMS Bridge Wizard for precise capacity