

ED9732(64)H5NV-2

32/64CH TITANIUM 4K NETWORK VIDEO RECORDER

Specification:



Main Feature:

- Support 32/64 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
Playback : 16 CH simultaneously playback
- Search: time slice, time, event (manual, sensor, motion), tag search Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-user online simultaneously
- Authorization management, log review and device status review
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises. Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS

Model	ED9732H5NV-2	ED9764H5NV-2	
System	Compression	Standard H.265	
	OS	Embedded Linux	
Video	Network Input	32 CH IPC input	64 CH IPC input
	Network Access Bandwidth	256Mbps	320Mbps
	Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps	
	Output	HDMI × 2 : one of 4K × 2K / 1920 × 1080 / 1280 × 1024 the other of 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024	
Audio	Network Input	32 CH IPC audio input	64 CH IPC audio input
	2-way Audio	RCA × 1	
	Local Output	RCA × 1	
Record	Record Stream	Dual stream recording	
	Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P	
Playback	Mode	Manual, timer, motion, sensor	
	Simultaneous Playback	Max 16 CH	
	Search	Time slice / time / event / tag search	
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events	
Alarm	Function	Play, pause, FF, FB, digital zoom, etc.	
	Mode	Manual, sensor, motion, exception	
	Input	8 CH local alarm input, support IPC alarm input	
Network	Output	4 CH	
	Triggering	Record, snap, preset, e-mail, etc.	
	Interface	RJ45 10 / 100 / 1000 Mbps × 2	
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP	
Mobile Device	Web Client	Max 10 users online	
	OS	iOS, Android	
Storage	HDD	SATA × 8, e-SATA × 2, max 10T per HDD	
	Local Backup	U disk, USB mobile HDD	
Backup	Network Backup	Yes	
	USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel), USB 3.0 × 1 (rear panel)	
Port	Remote Controller	Yes	
	Power Supply	ATX	
Others	Consumption	≤ 15W (without HDD)	≤ 15W (without HDD)
	Dimensions (mm)	430 × 453 × 89 (W × D × H)	
	Work Environment	-10 ~ 50 , 10% ~ 90% humidity	

Physical Interfaces:

