

-GENESIS-

Riser Rated Security & Control Cable Part Number: 2218

18 AWG 10 Stranded Conductors Shielded

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 18 AWG 19 Strand Bare Copper
Conductor Count 10
Insulation Polypropylene (0.006" nom.)
Insulation Colors Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray
Lay Length 4.75" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.017 " nom.)
Overall Diameter 0.268" nom.
Print Legend GENESIS P/N 2218 10C 18AWG SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR
C(ETL)US FT4 SUN RES 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1
2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 6.66 Ohms/1000' at 20°C
Capacitance 22.7 pF/ft. nom.
Impedance 47 Ohms nom.

Temperature -20°C to 75°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes

Country of Origin USA