

-GENESIS-

Plenum Rated Security & Control Cable

Part Number: 3224

14 AWG 4 Stranded Conductors Shielded

Ratings CL3P, FPLP, FT6

Approvals ETL Listed

Construction

Conductor 14 AWG 19 Strand Bare Copper

Conductor Count 4

Insulation Plenum PVC (0.008" nom.)

Insulation Colors Black, Red, White, Green

Lay Length 4.25" nom.

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket Plenum PVC (0.015 " nom.)

Overall Diameter 0.238" nom.

Print Legend GENESIS P/N 3224 4C 14AWG SHIELDED 3038058 (ETL) CL3P OR FPLP FT6 75C (RoHS)
W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.

DC Resistance 2.62 Ohms/1000' at 20°C

Capacitance 58.6 pF/ft. nom.

Impedance 31 Ohms nom.

Temperature -20°C to 75°C

Flame Rating NFPA 262 (Plenum); CSA C22.2 No. 2556 (FT6)

RoHS Compliant Yes

Country of Origin USA