

GV-AS ID Card / GV-AS ID Key Fob / GV-UHF Tag / GV-Patrol Tag



GV-AS ID Card is ideal for business environment where identity and access control are important for security reasons. GV-AS ID Key Fob, designed for easy carrying and key replacement, is ideal for residential application. GV-UHF Tag is ideal for parking lot management. GV-Patrol Tag is ideal as easily-installed patrol sites with high mobility. These access cards, key fobs and tags are compatible with the devices below.

KEY FEATURES

- 125 KHz Card / Key Fob
- 13.56 MHz ISO 1444-3A Card / Key Fob / Patrol Tag
- 900 MHz ISO 18000-6C Tag

Model Name	Frequency	Compatible Devices
GV-AS ID Card / GV-AS ID Key Fob	125 KHz	GV-Reader: GV-Reader 1251 / GV-SR1251 GV-Enrollment Reader: GV-PCR1251
GV-AS ID Card / GV-AS ID Key Fob		GV-AS Controller: GV-AS100 / GV-AS1010 / GV-AS110 / GV-AS1110 / GV-AS120 / GV-CS1320
GV-AS ID F Card / GV-AS ID F Key Fob	13.56 MHz	GV-Reader: GV-Reader 1352 V2 / GV-CR420 / GV-CR1320 GV-DFR1352 / GV-R1352 / GV-RK1352 GV-GF Fingerprint Reader (Card Only Mode): GV-GF1911 / GV-GF1912 / GV-GF1921 / GV-GF1922
GV-Patrol Tag		GV-Enrollment Reader: GV-PCR1352
GV-UHF Tag	900 MHz	GV-UHF Reader: GV-RU9003

Note: The hole option of the GV-AS ID Card is only available for 13.56 MHz ISO 1444-3A.

Model Name	Dimensions	Operating Temperature
GV-AS ID Card & GV-AS ID F Card	85.5 x 54 mm (3.4" x 2.1")	-20 ~ 70°C (-4 ~ 158°F)
GV-AS ID Key Fob & GV-AS ID F Key Fob	30.5 x 37.5 mm (1.2" x 1.5")	-20 ~ 55°C (-4 ~ 131°F)
GV-Patrol Tag	34 x 6 mm (1.3" x 0.2")	-45 ~ 85°C (-49 ~ 185°F)
GV-UHF Tag	97 x 12 mm (3.8" x 0.5")	-20 ~ 85°C (-4 ~ 185°F)