

GV-IO Box 4 Ports V1.2



The GV-IO Box 4 provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications		
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2
Compatible S/W		GV-System version 8.5.7 or later
Input	Input	4
	Input Signal	Dry Contact Wet Contact, 9-30V AC/DC
Communication	Relay Output	4
	Relay Status	Normal open
	Relay Capacitance	USB Connection
RS-485 Connection		125 / 250V AC, 3A 30V DC, 3A
DC IN		DC 12V, 1A
Address		0-9, A-F
Terminal Resistance		120 ohm
Environmental Conditions		0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)
Dimensions (W x H x D)		111.4 x 27.5 x 101 (mm) / 4.39 x 1.08 x 3.98 (in)
Installation Guide		GV-IO Box 4

Note: All specifications are subject to change without notice.

Packing List

1. GV-I/O Box 4 Ports V1.2 x 1
2. USB Cable (Type A to B) x 1
3. Terminal Resistor x 1
4. Power Adapter DC 12V x 1
5. Software DVD x 1