

PRO3200

Professional Series Access Modules

SPECIFICATIONS

Dimensions:

- Board: 9.0" H x 5.5" W x 1.0" D (22.9 cm H x 14 cm W x 2.5 cm D)
- PRO22ENC1: 13.9" H x 17" W x 9" D (35.3 cm H x 43.2 cm W x 22.9 cm D)
- PRO22ENC2: 13.9" H x 18.9" W x 9" D (35.3 cm H x 48 cm W x 22.9 cm D)
- PRO22ENC3: 14" H x 16" W x 4" D (35.6 cm H x 40.6 cm W x 10.2 cm D)
- PRO22ENC4: 8.37" H x 7.63" W x 7.63 D (21.28 cm H x 19.4 cm W x 19.4 cm D)
- PRO22ENC5: 9.35" H x 16.85" W x 5.6" D (23.7 cm H x 42.8 cm W x 14.2 cm D)

Environment:

- Temperature: 0°C to 49°C operational; -55°C to 85°C storage
- Humidity: 0 to 85% RHNC

Wire Requirements:

- Power - twisted pair, 18 AWG
- RS485 - 24 AWG, 4,000 ft (1,200m) max, two twisted pairs with shield (120 ohms, 23 pF, Belden 9842 or equiv)
- RS-232 - 24 AWG, 25 ft (7.6m) max
- Alarm input - twisted pair, 30 ohms max

Enclosures:

- PRO22ENC1 (Wall-mount) Capacity: 9 modules. Power supply and battery not included
- PRO22ENC2 (19" Rack-mount) Capacity: 9 modules. Power supply and battery not included
- PRO22ENC3 (Tile-mount) Capacity: 2 modules. Power supply and battery included
- PRO22ENC4 (Tile-mount) Capacity: 1 module (PRO22R1 only). Power supply and battery included
- PRO22ENC5 (Cage only for custom enclosures) Capacity: 9 modules. Power supply and battery not included

ORDERING

PRO3200 Controllers

PRO32IC	PRO3200 Intelligent Controller
PRO22R1	PRO2200 Single Reader Module
PRO32R2	PRO3200 Dual Reader Module
PRO32OUT	PRO3200 16 Relay Output Module
PRO32IN	PRO3200 16 Alarm Input Module

PRO-Series Enclosures

PRO22ENC1	(Wall-mount) Capacity: 9 modules. Power supply and battery not included
PRO22ENC2	(19" Rack-mount) Capacity: 9 modules. Power supply and battery not included
PRO22ENC3	(Tile-mount) Capacity: 2 modules. Power supply and battery included
PRO22ENC4	(Tile-mount) Capacity: 1 module (PRO22R1 only). Power supply and battery included
PRO22ENC5	(Cage only for custom enclosures) Capacity: 9 modules. Power supply and battery not included

PRO3200 Starter Kit with Software

PRO32SKD8	8 Door Starter Kit (1) PRO32E1D8 with WIN-PAK SE Software
------------------	---

PRO3200 Expansion Kits

PRO32E1D2	2 Door Kit (1) PRO32R2, (2) S-4 and (1) PRO32E1EN
PRO32E1D4	4 Door Kit (2) PRO32R2, (4) S-4 and (1) PRO32E1EN
PRO32E1D8	8 Door Kit (4) PRO32R2, (8) S-4 and (1) PRO32E1EN

Optional Accessories

PRO22DCC	Daisy Chain cable required for PRO22ENC1, PRO22ENC2 and PRO22ENC5
PRO32E1PS	4 A rack-mounted power supply with battery backup required for PRO22ENC1, PRO22ENC2 and PRO22ENC5

Network Kits

PRO32E1EN	Includes: PRO22ENC1, PRO32IC, PRO32E1PS, PRO22BAT1 and PRO22DCC
PRO32E2EN	Includes: PRO22ENC2, PRO32IC, PRO32E1PS, PRO22BAT1 and PRO22DCC

For more information: www.honeywellaccess.com

Automation and Control Solutions

Honeywell Security Products Americas
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
1.800.323.4576
www.honeywell.com

L/PRO3200AMD/D
April 2014
© 2014 Honeywell International Inc.

Honeywell