



**Overview:**  
Wi-Fi 9000 with Voice Control,  
7 Day Programmable Thermostat

### Features:

- **Voice Activated Recognition and Control** (on-device only) allows the temperature setting to be adjusted in the home by talking to the thermostat
- **Total Connect Comfort App** - Allows user to remotely monitor and manage home's comfort and energy usage anytime, anywhere
- **On-screen Comfort Information** - See indoor and outdoor temperature and humidity information right on the home screen
- **Customizable Color Touchscreen** - Easily change the high-definition display to any color you choose
- **Auto Alerts** - Extreme temperature alerts and filter change reminders are sent to connected network devices and displayed on thermostat
- **Advance Fan/Control Comfort** - Improves air circulation and helps regulate the temperature throughout your home
- **Energy Savings** - Choose programmable mode to save on annual heating and cooling costs
- **Internet Time Sync** - Keeps time during power failure and automatically updates for daylight savings
- **Simple Programming** - Tool-free wiring, manual-free install and setup
- **5 Year Limited Warranty**



**TH9320WFV6007**  
Wi-Fi 9000 Thermostat with  
Voice Control

**Product Specifications:**

|                                        |                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------|
| <b>Application/Stages</b>              | Up to 3 Heat/2 Cool Heat Pumps;<br>Up to 2 Heat/2 Cool Conventional Systems         |
| <b>Programmability</b>                 | 7-Day multiple day programming or non-programmable                                  |
| <b>Dimensions</b>                      | 3-1/2" (H) x 4-1/2" (W) x 7/8" (D)                                                  |
| <b>Used With</b>                       | THP9045 Wire Saver                                                                  |
| <b>Comments</b>                        | Tri-Lingual display (selectable for English, French or Spanish)                     |
| <b>Mounting</b>                        | Horizontal                                                                          |
| <b>Electrical Rating</b>               | 18 to 30 Vac                                                                        |
| <b>Frequency</b>                       | 50 Hz; 60 Hz                                                                        |
| <b>Operating Humidity Range (% RH)</b> | 5 TO 90% RH, non-condensing                                                         |
| <b>Supply Voltage</b>                  | 18 to 30 Vac                                                                        |
| <b>Switch Positions</b>                | Systems: HEAT-OFF-COOL-AUTO-EM.HEAT<br>Fan: AUTO-ON-CIRC-FOLLOW SCHEDULE            |
| <b>Operating Temp. Range</b>           | 32°F to 120°F (0°C to 48.9°C)                                                       |
| <b>Color</b>                           | Black                                                                               |
| <b>Power Method</b>                    | Hardwired                                                                           |
| <b>Terminal Designations</b>           | R, RC, C, W (O/B), W2 (AUX/E), Y, Y2, G, L                                          |
| <b>Display</b>                         | 8.06 sq. in. color Touchscreen                                                      |
| <b>Scheduling</b>                      | Online scheduling or locally at thermostat                                          |
| <b>Changeover</b>                      | Auto or manual                                                                      |
| <b>Setting Temperature Range</b>       | Heat: 40°F to 90°F; Cool: 50°F to 99°F<br>(Heat: 4.5°C to 32°C; Cool: 10°C to 37°C) |