

11W Explosion Proof LED Lamp - Wire Guard - Surface Mount - ATEX/IECEX ATEX-EPL-LP-12-LED-WG-R1

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



ATEX-EPL-LP-12-LED-WG-R1 Flameproof LED Lamp

Listing: NRTL Listed for International; ATEX/IECEX Rated

Lamp Technology: LED

Dimensions: 17.59"L x 3.36OD

Weight: -

Voltage: 100-250 V AC, 12-48 V DC, 48-72 V AC, 12-36 V AC, 70-110 V DC, 125 V DC, or 250 V DC

Watts: 11W

Lumens: -

Luminous Efficiency: -

Life Expectancy: 50,000+ hours

Light Color: White

Color Rendering Index: -

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Beam Type: Full

Lighting Configuration: Flood

Efficiency: -

Power Factor: -

Protection: Wire Guard

Amp Draw: 0.09 A @ 120 V, 0.04 A @ 250 V

Ambient Operating Temp Range: -40°C to +40°C/+55°C

Housing Material: Alloy Plastic

Mounting: Surface Mount

Protection: Wire Guard

Ratings/Approval

Approved for Zone 1 & Zone 2

Approved for Zone 21 and Zone 22

Ex db eb II C T5 Gb

Ex tb IIIC T95 Db (Ta55)

NRTL Certified to IEC 60079

NRTL Certified to EN 60079

Special Orders - Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics ATEX-EPL-LP-12-LED-WG-R1 Explosion Proof LED Surface Mount Lamp enables operators in ATEX/IECEX rated environments to closely illuminate hazardous areas effectively. The solid-state, 11-watt LED light is protected by a stainless steel mesh wire guard for added durability.

The ATEX-EPL-LP-12-LED-WG-R1 is a powerful lighting solution for Zone 1/Zone 2 and Zone 21/Zone 22 rated work sites. This 11-watt LED lamp takes on a slim, cylindrical form factor and is protected by a stainless steel wire guard. A full, 360-

degree lighting configuration ensures comprehensive illumination during use. This ATEX/IECEX rated light weight explosion proof light is constructed of alloy plastic. Applications for this light includes: repair lighting in hazardous locations, mobile or temporary illumination, task lighting, inspections and more.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Voltage: The ATEX-EPL-LP-12-LED-WG-R1 operates on 100-250 V AC, 12-48 V DC, 48-72 V AC, 12-36 V AC, 70-110 V DC, 125 V DC, or 250 V DC.

Mounting: The ATEX-EPL-LP-12-LED-WG-R1 is designed to be surface mounted. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

Options:

ATEX-EPL-LP-12-LED-WG-R1-Voltage

Example: ATEX-EPL-LP-12-LED-WG-R1-1227

Voltage	
100-250V AC	-1227
12-48V DC	-1224-DC
48-72V AC	-48V-AC
12-36V AC	-1224-AC
70-110V DC	-72V-DC
125V DC	-125VDC
250V DC	-250VDC



Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)