

Cord Grip (to use with EYM) to seal off wiring connections to explosion proof lights

CGB-50

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Cord Grip (to use with EYM) to seal off wiring connections to explosion proof lights

• .125-.187"	• Red
• .187-.312"	• Brown
• .312-.437"	• Yellow
• .375-.500"	• Purple
• .500-.625"	• Pink
• .625-.750"	• Orange

The above table shows the outside diameter of the customer's cord and the corresponding color of the cord grip that is appropriate for a cord of that diameter.

Common Cord Type Diameters

• 18 AWG			
• 16 AWG			
• 14 AWG			
• 12 AWG			
• 10 AWG			



• 8 AWG				
• 6 AWG				
• 4 AWG				
• 2 AWG				
• 1 AWG				



Frequently Asked Questions (FAQ)





Options:

CGB-50-Wire Size

Example: CGB-50-RED

Wire Size	
.125-.187	-RED
.187-.312	-BRN
.312-.437	-YLW
.375-.500	-PRP
.500-.625	-PNK
.625-750	-ORG

Links (Click on the below items to view):

- [Operations Manual](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)