

Cord Grip (to use with EYM) to seal off wiring connections to explosion proof lights
CGB-75

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Cord Grip (to use with EYM) to seal off wiring connections to explosion proof lights

| | |
|--------------|----------|
| | |
| • .125-.250" | • Blue |
| • .250-.375" | • Green |
| • .375-.500" | • Purple |
| • .500-.625" | • Pink |
| • .625-.750" | • Orange |
| • .750-.875" | • Grey |

The above table shows the outside diameter of the customer's cord and the corresponding color of the cord grip that is appropriate for a cord of that diameter.

Common Cord Type Diameters

| | | | |
|----------|--|--|--|
| | | | |
| • 18 AWG | | | |
| • 16 AWG | | | |
| • 14 AWG | | | |
| • 12 AWG | | | |
| • 10 AWG | | | |



| • 8 AWG | | | | |
|---------|--|--|--|--|
| • 6 AWG | | | | |
| • 4 AWG | | | | |
| • 2 AWG | | | | |
| • 1 AWG | | | | |



Frequently Asked Questions (FAQ)





Options:

CGB-75-Wire Size

Example: CGB-75-BLU

| Wire Size | |
|-----------|------|
| .125-.250 | -BLU |
| .250-.375 | -GRN |
| .375-.500 | -PRP |
| .500-.625 | -PNK |
| .625-.750 | -ORG |
| .750-.875 | -GRY |

Links (Click on the below items to view):

- [Operations Manual](#)
- [STEP File \(3D CAD Model\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)