

29" Hazardous Location Stainless Steel Flex Coupling - C1D1, C2D1 - 1.5" NPT Male/Male - ATEX/IECEx

CLP-SS-1.5-29-FLX-M2M

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



CLP-SS-1.5-29-FLX-M2M Stainless Steel Flex Coupling

Unit Type: Stainless Steel Flex Coupling Dimensions: 35.125" -L x 2.781" -D Weight: -Flexible Length:29" Minimum Bend Radius: 16" Materials: Stainless Steel (316SS, 304SS, 321SS), Silicone-coated Fabric (Internal Liner) Conduit Size:1.5"

Features/Ratings

Class I, Divisions 1 & 2 Groups A,B,C,D Class I, Zone 1 Groups IIB, IIA Class II, Divisions 1 & 2 Groups E,F,G Class III IECEx SIR 10.0057U SIRA 10ATEX11068U 0539 II 2GD Ex d IIC Gb, Ex t IIIC Db IP66

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics CLP-SS-1.5-29-FLX-M2M Hazardous Location Stainless Steel Flex Coupling is designed for flexible connections and positioning of conduit systems in explosive environments. This accessory measures 35.125" and offers a minimum bend radius of 16". The IP66rated unit is constructed of stainless steel.

The CLP-SS-1.5-29-FLX-M2M offers versatile positioning of connections and components for conduit systems in hazardous locations. Featuring a 16" minimum bend radius, this unit provides a flexible length of 29". The accessory measures 35.125" long with a 1.5" conduit opening. The flexible coupling is constructed of stainless steel (316SS NPT male fittings, 304SS outer braid and 321SS inner flex hose). The internal liner is made out of silicone-coated fabric.

This hazardous location unit is suitable for Class I, Divisions 1 & 2; Class I, Zone 1; Class II, Divisions 1 & 2 and Class III work sites. The IP66-rated accessory also meets ATEX/IECEX guidelines.

Applications: Petroleum refineries, chemical and petrochemical plants, paint spray booths, food manufacturing buildings, automotive repair, flour/grain processing and storage centers, industrial facilities, conduit systems and more. At Larson Electronics, we do more than meet your lighting needs. We also provide

Larson Electronics LLC 9419 E US HWY 175, Kemp, TX 75143 Phone: 800.369.6671



replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message <u>sales@larsonelectronics.com</u> for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)



Links (Click on the below items to view):

- ATEX Certificate (European Explosion Proof)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- IEC Ex Certificate (International Explosion Proof)
- MSDS (Material Safety Data Sheet
- Operations Manual
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- ISO 9001 Certification
- Business Certificate