

30A Explosion Proof Fused Disconnect - Fast Acting Fuse - (3) 30A 250V - (2) 1" NPT Hubs - N4X EPFDS-V2-30A-3P-3X30A.250V-FA

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



EPFDS-V2-30A-3P-3X30A.250V-FA Explosion Proof Disconnect Switch / Breaker

Unit Type: Explosion Proof Disconnect Switch (Fused)

Dimensions: 8" x 10" x 6"

Weight: -

Rated Voltage: 250V AC

Configuration: 3-Pole

Fuse Type: Fast Acting Fuse

Fuses: (3) 30A 3P [250V]

Cover Type: Flat Aluminum Plate

Materials: Copper-free Aluminum, Stainless Steel (External Hardware)

Mounting: Surface Mount via Mounting Pan

Hub Sizes: (2) 1" NPT

Conduit: Operator Provided

Color: Gray

Ratings

Class I, Divisions 1&2 Groups B,C,D

Class I, Zones 1&2 Groups IIB+H2,IIA

Class II, Divisions 1&2 Groups E,F,G

Class III

Type 4, 4X

Ex II 2 G Ex db IIB+H2 T6

Ex II 2 D Ex tb IIIC T85°C IP66

Ta -50°C to + 70°C

ATEX & IEC Ex

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

The Larson Electronics EPFDS-V2-30A-3P-3X30A.250V-FA Explosion Proof Fused Disconnect is designed for use in Class I, II and III environments. Equipped with fast-acting fuses, this 3-pole unit contains three, 30-amp 250V fuses and two, 1" NPT hubs. The explosion proof disconnect offers instant response to surges and electrical spikes, making it ideal for resistive circuits in flammable work sites.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES

The EPFDS-V2-30A-3P-3X30A.250V-FA ensures active protection of electrical systems in combustible facilities. This fused unit contains three, 30-amp 3-pole 250V fast-acting fuses. These explosion proof disconnects are sensitive to electrical pulses, which provide peace of mind for operators working with sensitive equipment, such as laptops and electronics. Choosing between a time-delay fuse and a fast-acting fuse highly depends on the type of system or device requiring protection, as both protective methods are effective (one is not superior over the other).

This explosion proof disconnect switch/breaker is made of copper-free aluminum with stainless steel external hardware and features a flat aluminum plate (bolted)

cover for uniform and attractive installations.

Hubs: For completing electrical connections, two 1" NPT hubs are provided on the enclosure.

Mounting: Operators can mount the explosion proof disconnect on flat surfaces, which is facilitated by a mounting pan.

Applications: Sensitive equipment, electronics, LED lighting systems, computers, petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)