

## 30A Explosion Proof Fused Disconnect - Time Delay Fuse - (3) 30A 600V, (2) 1" NPT Hubs - N4X EPFDS-V2-30A-3P-3X30A.600V-TD

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



### EPFDS-V2-30A-3P-3X30A.600V-TD Explosion Proof Disconnect Switch / Breaker

**Unit Type:** Explosion Proof Disconnect Switch (Fused)

**Dimensions:** 8" x 10" x 6"

**Weight:** -

**Voltage:** 600V AC or 125V DC (Maximum)

**Configuration:** 3-Pole

**Amps:** 30A

**Fuse Type:** Time Delay Fuse

**Time Delay:** 10 Seconds (Minimum) @ 500% Overload

**Fuses:** (3) 30A 3P [600V]

**Cover Type:** Flat Aluminum Plate

**Materials:** Copper-free Aluminum

**Hardware Materials:** Stainless Steel

**Mounting:** Surface Mount via Mounting Pan

**Hub Qty:** 2

**Hub Sizes:** (2) 1" NPT Hubs

**Conduit:** Operator Provided

**Color:** Gray

\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

### Ratings

Class I, Divisions 1&2 Groups B,C,D

Class I, Zones 1&2 Groups IIB+H2,IIA

Class II, Divisions 1&2 Groups E,F,G

Class III

Type 4, 4X

Ex II 2 G Ex db IIB+H2 T6

Ex II 2 D Ex tb IIIC T85°C IP66

Ta -50°C to + 70°C

ATEX/IECEX

### Special Orders- Requirements

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-214-616-6180

**Fax:** 1-903-498-3364

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The Larson Electronics EPFDS-V2-30A-3P-3X30A.600V-TD Explosion Proof Fused Disconnect is designed for use in Class I, II and III environments. Equipped with time-delay fuses, this 3-pole unit contains three, 30-amp 600V fuses and two NPT hubs. The explosion proof disconnect offers delayed response to transient surges, making it ideal for addressing pulse currents and temporary overloads associated with motors, HVAC systems and HID lights in flammable work sites.**

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES\***

The EPFDS-V2-30A-3P-3X30A.600V-TD ensures active protection of electrical systems in combustible facilities. Designed to operate on 600V AC or 125V DC (maximum), this fused unit contains three, 30-amp 3-pole 600V time-delay fuses. The fuses feature 10-second time delay at 500% overload. These explosion proof disconnects are not sensitive to electrical pulses, allowing connected systems to utilize more power without activating the fuse. Time-delay fuses (also known as a short-blow fuse or a slow-blow fuse) can withstand electrical surges for a specific period of time, typically 10-15 seconds. This feature is useful for equipment that

---

relies on high voltage current during startup, such as motors.

Choosing between a time-delay fuse and a fast-acting fuse highly depends on the type of system or device requiring protection, as both protective methods are effective (one is not superior over the other).

The explosion proof disconnect switch/breaker is made of copper-free aluminum with stainless steel external hardware and features a flat aluminum plate (bolted) cover for uniform and attractive installations. A NEMA 4X rating provides protection against corrosion from water and the formation of ice, the ingress of dust and external foreign objects.

**Hubs:** For completing electrical connections, two 1" NPT hubs are provided on the enclosure.

**Mounting:** Operators can mount the explosion proof disconnect on flat surfaces, which is facilitated by a mounting pan.

**Applications:** Motors, VFDs, phase converters, HVAC systems, dryers, fluorescent lights, HID lights, metal halide, high pressure sodium, mercury vapor, petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---



---

## Frequently Asked Questions (FAQ)

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)