

Explosion Proof Junction Box - 5 Hub Pull Box - Class 1 Div 1 & 2

EPJB-5

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Explosion Proof 3/4" Rigid Conduit Fitting

This explosion proof junction box is used to branch threaded rigid conduits in hazardous locations. This explosion proof junction box features five 3/4" opening to provide a variety of hubs with a low profile design for locations with limited space. Percision cast and machined surface permit safer wire pulling. Percision NPT threaded hubs allow trouble-free field installation for this rigid conduit box. The cover seals to the box with a standard O ring gasket to make this explosion proof pull box a raintight enclosure.

Specs:

Body Material: iron alloy

Cover Material: copper-free aluminum.

Hub size: 3/4"

Ratings:

Class 1, Divisions 1 & 2, Groups C & D

Class 2, Division 1, Groups E, F, G

Class 2, Division 1, Groups F, G

Class 3, Divisions 1 & 2

UL 886

Frequently Asked Questions (FAQ)









Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)