

## C1D1 Explosion Proof Enclosure - 6" x 6" x 4" Internal Dims, Surface Mount - (8) Hubs

EPL-AEA-6.6.4-4X.75E-4X.75W

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



### EPL-AEA-6.6.4-4X.75E-4X.75W Explosion Proof Enclosure

**Listing:** NRTL Listed for United States, Canada

**Internal Dimensions:** 6" (152mm) L x 6" (152mm) H x 4" (102mm) D

**External Dimensions:** 10.32" (262.13mm) L x 10.32" (262.13mm) H x 6.09" (154.69mm) D

**Pan Dimensions:** 5" (127.0mm) L x 5" (127.0mm) W

**Available Dimensions for Devices:** 5.73" (145.5mm) L x 5.73" (145.5mm) H x 4.31" (109.47mm) D

**Weight:** 18 lbs (8.17 kgs)

**Maximum Conduit Size:** 2" NPT

**Maximum Operators on Lid:** 4 (2 rows of 2)

**Total Hub Quantity:** (8) 3/4" NPT

**Lid (Top) Hubs:** 0

**North Side Hubs:** 0

**South Side Hubs:** 0

**East Side Hubs:** (4) 3/4" NPT

**West Side Hubs:** (4) 3/4" NPT

**Bottom (Back/Base) Hubs:** 0

**Conduit:** Operator Provided

**Operating Window:** N/A

**Hinges Included:** No

**Hinges Material:** N/A

**Internal Mounting Pan Included:** N/A

**Internal Mounting Pan Taps:** N/A

**Internal Mounting Pan Material:** N/A

**Internal Mounting Pan Dimensions:** N/A

**Internal Grounding Lug:** N/A

**Breather Plug:** N/A

**Drain Plug:** N/A

**Suggested Operator Series:** Long Length

**Ambient Operating Temp Range:** -30Â° C to +85Â° C

**Operating Temp Rating:** T5/T6 Rated

**Enclosure Material:** Copper Free Cast Aluminum (less than 4/10 of 1%)

**Hardware Material:** Zinc Plated Steel

**Enclosure Finish:** Aluminum Lacquer Paint; Custom Available

**Mounting:** Surface Mount Legs

**Mounting Leg Height:** 0.25"

**Mounting Dimensions Height:** 4.00" (101.60mm) Center to Center

**Mounting Dimensions Width:** 7.88" (200.15mm) Center to Center

**Shipping Weight:** 78 lbs

**Shipping Dimensions:** 48"L x 48"W x 21"H

### Features/Ratings

Listed for NEC and CEC

Class I, Divisions 1 & 2, Groups B\*\*, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Divisions 1 & 2, Groups E, F, G

Class III, Divisions 1 & 2

NEMA 3R, 4, 7, 9

NRTL Certified to UL 886

NRTL Certified to UL 698

NRTL Certified to UL 1203

NRTL Certified to CSA C22.2 No 30

\*\*Conduit seals required within 18" for Group B applications

**Replacement Internal Mounting Pan:** %PAN%

### Special Orders- Requirements

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-214-616-6180

**Fax:** 1-903-498-3364

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

**The EPL-AEA-6.6.4-4X.75E-4X.75W from Larson Electronics is an Explosion Proof Enclosure that provides operators with a Class I and II, Divisions 1 and 2 cast aluminum enclosure designed to hold electrical equipment up to 6" by 6" by 4" in size. This explosion proof enclosure is ideal for indoor or outdoor applications where flammable vapors, gases, or dusts exist or stand the potential to exist.**

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES\***

The EPL-AEA-6.6.4-4X.75E-4X.75W explosion proof enclosure is made of cast aluminum, equipped with steel bolts and includes a weatherproof gasket for a NEMA 3R / NEMA 4 protection rating. This hazardous location device enclosure box is NEMA 7 (Groups B, C, and D) and NEMA 9 (Groups E, F, and G) rated. The internal cavity of this flameproof enclosure measures 6" in length by 6" in width by 4" in height. A backplate is available for this unit at an extra cost. Message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information or call us today at 800-369-6671.

There is a total of eight evenly spaced 3/4" NPT hubs on the enclosure: (4) 3/4" NPT on the east side and (4) 3/4" NPT on the west side.

This explosion proof enclosure is designed to house a wide range of compact electronics, control stations, meters, relays, starters, circuit breakers, terminal blocks and industrial equipment, for safe use in combustible work sites. Other applications include systems requiring junction, pull and/or splice boxes.

---

#### Click Photos to Enlarge

[Click To Enlarge](#)

[Click To Enlarge](#)

*Larson Electronics can customize each unit with drilled and tapped operator hubs and/or conduit hubs per customer request. Please view the above and below images for orientation. When looking at the top cover (labeled Lid), all four sides are labeled for the orientation when looking at the Lid. All hubs are CNC machined for precision. Please see below specifications table for included taps and dimensional drawing for exact locations.*

[Click To Enlarge](#)

[Click To Enlarge](#)

---

**Construction:** Each unit in the EPL-AED series is certified to NEC standards for United States and CEC Canada. We offer an ATEX/IEC Ex model for global applications (ATEX-EPL-AED series). These explosion proof enclosures are NEMA 3R rated, for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4X equipment can be equipped upon request. NEMA 4X models include all stainless steel external hardware. Operator lid hinges can be fitted on the enclosure for regular opening and closing. Breather plugs, drain plugs, and grounding lugs can be added at customer request.

**Customization:** Larson Electronics can customize this explosion proof enclosure for compatibility with existing systems, assemblies, work flows and processes or assist in designing units for new installation. We can add indicator lights, windows, hinges, operator handles, push button switches, momentary push button switches, emergency stop push buttons, selector switches, on/off switches, terminal blocks, relays, PLCs, mounting pans and more. Customized labels are also available for each operator in order to meet various requirements.

Conduit openings can be tapped on all sides and back of the explosion proof enclosure. Tapping of conduit hubs is facilitated at Larson Electronics using a CNC machine for precise cutting. Larson Electronics offers customization on conduit opening size and locations. Taps include female NPT (National Pipe Thread), female BSPT (British Standard Pipe Thread), and Metric ISO thread. Please contact us for specific requirements. Additional equipment can be provided from factory, including nipples, unions, seal-offs, and operator devices.

**Suggested Applications:** The EPL-AED series of explosion proof enclosures are

---

approved for use within indoor and outdoor environments where flammable or combustible gases, vapors, dusts, fibers, and flying exist or stand the potential to exist, and is ideal for a wide variety of applications.

Applications include but not limited to aircraft maintenance, alcohol processing, aerospace, chemical manufacturing, coke processing, cold storage, compressed natural gas (CNG) facilities, cranes, cryogenics, distilleries, food processing, fuel storage, gas processing plants, grain processing, laboratories, liquefied natural gas (LNG) facilities, liquid propane gas (LPG), machine operations, manufacturing, marine vessels, methane production, mining, offshore, oil drilling rigs, oil refineries, paint spray booths, paper processing, petrochemical, petroleum refineries, pharmaceuticals, power plants, production refineries, sand blast cabinets, sewage and septic tanks, shipyards, solvent and cleaning areas, storage facilities, tank farms, tankers, textile, washdown areas, waste treatment plants, and woodworking. [Click here to read the NEC description for explosion proof and hazardous locations.](#)

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---

---

## Frequently Asked Questions (FAQ)













Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)