

Explosion Proof - 3 Wire- 3 Pin- 60Amp- Receptacle Plug

EPP-3W-3P-60A-P

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



EPP-3W-3P-60A-P Explosion Proof PLug

Amp Rating: 60

Dimensions:7.81"-L 3.81 "-W

Configuration: 3 Pole 3 Wire

Suitable Cable Diameter: .500" to 1.375"

Certifications - Compliance

Class 1 Groups B, C and D

Class2 Groups F and G

Class 2 DIV 1 - 2 Group F & G

Class 3

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics EPP-3W-3P-60A-P Explosion Proof Plug

This explosion proof 3 wire 3 pin plug is compatible with our EPO-3W3P-60A power receptacles. This plug is rated for 60amps and is suitable for Class 1 Groups B, C and D and Class 2 Groups F and G. This explosion proof plug features non sparking aluminum construction, recessed brass pins with a special ground first and last design, and a 60 amp current rating.

[Click Photo to Enlarge](#)

Inter-Compatibility: These plugs are cross-interchangeable with Crouse Hind™ APJ plugs under catalogue number "APJ6375" and Hubble-Killark VERSAMATE® plugs under catalogue number "VP6375"

Any equipment requiring these C-H or H-K plugs should work with these plugs. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Motor-Generator Sets, Compressors, Wet areas or Locations Where Combustible Dust is Present.



Frequently Asked Questions (FAQ)









Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)