

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



EPSN-HRN-PA-MOD1-RED Explosion Proof Industrial Horn/Siren

Dimensions: 14" W x 8" H x 18.5" L

Weight: 19.5 lbs

Materials: Cast Aluminum/Fiberglass

Voltage: 120-240VAC or 24VDC

Amps: 0.8A 50/60 Hz @ 24VDC, 0.2A 50/60 Hz @ 120VAC, 0.1A 50/60 Hz @ 240VAC

Volume: S7-110dbA @ 10 feet

Mounting: Omni directional mounting bracket, 1/2" conduit access

Operating Modes: 8 User Selectable Field Tones

Ambient Temperature Range: -55° C to +85° C - -67° F to +185° F

Approvals

UL Listed

Class I, Division 1, Groups C & D

Class I, Division 2, Groups A, B, C, & D

Class II, Division 2, Groups F & G

NEMA 4X

Marine Rated

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPSN-HRN-PA-MOD1-RED explosion proof horn is constructed with an aluminum housing and fiberglass horn for durability and long life. This explosion proof horn/siren is weather and dust proof and Class 1 Division 1 groups C and D rated. This is a powerful alert and signal horn that offers multiple tones, remote operation capability, and multiple voltage options.

The Larson Electronics EPSN-HRN-PA-MOD1-RED explosion proof horn provides operators in hazardous locations with an effective and powerful alert/signal system that can withstand demanding conditions and be heard over the operation of industrial machinery. This unit includes 8 different tones which can reach peak output of 110dBA

and can be remotely operated for priority alerts.

The housing on this horn is constructed of heavy duty aluminum and the horn is formed fiberglass. The entire unit is finished in durable red powder coat for resistance to corrosion, is weatherproof/dustproof, and NEMA4x and marine rated for wet environments. Wiring is through a 1/2" conduit access hub, and the unit can be ordered in 120-240VAC configuration for use with standard voltages or 24 VDC for low voltage use. Mounting is via an omni directional bracket which allows mounting to flat surfaces and vertical adjustment of the horn for secure placement and optimum sound direction.

[Click Photos to Enlarge](#)

Tones: Selectable by switch on sound module

- 1) Continuously running train of eight sounds in sequence
- 2) Wail - conventional siren
- 3) Yelp - rapid siren
- 4) Two- tone
- 5) Whoop - ascending low to high
- 6) Yeow - descending high to low
- 7) Horn - Steady
- 8) Beep - slow intermittent horn
- 9) Stutter - rapid intermittent horn
- 0) Remote-Enables remote selection of:
 - 7 - Horn
 - 4 - Two tone - alternating
 - 3 - Yelp - rapid siren
 - 1 - Wail - manual siren

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Frequently Asked Questions (FAQ)

Options:

-Voltage

Example: -120V

Voltage	
120V AC	-120V
240V AC	-240V
24VDC	-24VDC

Links (Click on the below items to view):

- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)