

**30A Explosion Proof Contactor - Class I, II, III - 120V AC, 1P Contactor - (2) 3/4" NPT Hubs -
ATEX/IECEX Rated -**

EXP-CTR-1P-30A-120V-12VC-2X0.75NS

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



EXP-CTR-1P-30A-120V-12VC-2X0.75NS Explosion Proof Contactor

Listing: United States, Canada, International

Device Type: Explosion Proof Contactor

External Dimensions: 9.13" x 9.63" x 7.18"

Weight: -

Voltage: 120V AC, 50/60 Hz

Amps: 30A

Poles: 1 Pole

Configuration: NO or NC

Coil Voltage: 12V DC

Material: Copper-free Aluminum

Enclosure Finish: Electrostatically Applied Powder Epoxy/Polyester Finish

Mount: Surface

Wiring: Contactors - Lugs

Hubs: (2) 3/4" NPT Hubs

Hub Location: (1) North, (1) South

Access Hole OD: 5.38"

Ratings/Approvals

Class I, Division 1&2 Groups B,C,D

Class I, Zones 1&2 Groups IIB+H2,IIA

Class II, Division 1&2 Groups E,F,G

Class III

ATEX/IEC Ex

Ex d IIC T6 or T5

Ex tD A21 IP66 T80°C or T90°C IP66

Ta = -20°C to +60°C

NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)

Special Orders- Requirements

Contact us for special requirements

Phone: 1-214-616-6180

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EXP-CTR-1P-30A-120V-12VC-2X0.75NS from Larson Electronics is an Explosion Proof Contactor for secure connections to circuits and motors in ATEX-rated and combustible sites. This 30-amp device is compatible with 120V AC, 50/60 Hz and features a normally open or normally closed configuration. Operators are provided access to two 3/4" NPT hubs at the north and south sides of the explosion proof unit.

The EXP-CTR-1P-30A-120V-12VC-2X0.75NS facilitates electrical connections in flammable environments. This 30-amp, 1-pole unit operates on 120V AC, 50/60 Hz. Offered in a normally open or normally closed configuration, the explosion proof contactor features lugs for secure connections. The coil voltage of the device is 12V DC.

Constructed of copper-free aluminum with an electrostatically applied powder epoxy/polyester finish, this explosion proof contactor is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining robust and easy to use.

Hubs: Two, 3/4" NPT hubs are available on the north and south sides (1 per side) of the ATEX rated device. This unit is compatible with surface mount applications.

Applications: Hazardous locations, HVAC systems, industrial motors, compressors, chemical processing, welding, heating equipment, manufacturing sites and more.



At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

Options:

EXP-CTR-1P-30A-120V-12VC-2X0.75NS-Contact Config

Example: EXP-CTR-1P-30A-120V-12VC-2X0.75NS-NO

Contact Config	
NORMALLY OPEN	-NO
NORMALLY CLOSED	-NC



Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)