

**Explosion Proof Network IP Camera - 4.0MP Resolution, Built-in Infrared - 20FPS - IP66
Rated/N4X - NDAA Compliant
EXPCMR-NDAA-IP-POE-4MP-IR**

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



EXPCMR-NDAA-IP-POE-4MP-IR Network Explosion Proof Camera - NDAA Compliant

Listing: NRTL Listed for United States & Canada

Dimensions: 8"L x 6"W x 13"H

Weight: -

Total Watts: 6.4W (Max)

Power Source: 12V DC \pm 25%, PoE (IEEE802.3 af)

Image Sensor: 1/3" Progressive Scan CMOS Sensor

Main Stream Video Resolutions: up to 4MP (2592x1520) - Max. 20 fps; 4MP (2560x1440) - Max. 25 fps; 3MP (2048x1520) - Max. 30 fps

Sub Stream Video Resolution: up to 2MP (1920x1080) - Max. 30 fps

Mobile Data-Sensitive Stream Video Resolution: up to D1 (720x576) - Max. 30 fps

Compression Type: H.265, H.264, MJPEG

Bit Rate: 32Kbps - 8Mbps

Focal Length: 4.0mm @ F1.8

Bit Rate: 32Kbps - 16Mbps

Max Field of View: 80.8° of horizontal coverage; (45° vertical)

Shutter Speed: Auto/Manual, 1/6 to 1/100,000 second

Min. Illumination: Color video until 0.02 lux @F2.0, AGC ON 0 lux with IR on

Infrared Light: Built-in

Day/Night: IR-cut Filter w/ Auto Switch (ICR)

IR Range: up to 100'

Digital Noise Reduction: 2D/3D DNR

Ethernet Interface: RJ45 10M/100M Base-TX Ethernet

Protocols: IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP

BLC: Yes, Zone Configurable

Alarm Trigger: Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception

Ambient Temperature Range: -31°F to +140°F

Housing Materials: Copper-free Aluminum Alloy

Lens Material: 3/8" Thick Tempered Glass

Mounting: Adjustable rear-mounted handle/bracket

Wiring Hub: (2) 3/4" NPT

Shipping Weight: 13lbs

Ratings / Features

National Defense Authorization Act (NDAA) Compliant

Class I, Divisions 1 & 2, Groups B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Divisions 1 & 2, Groups E, F, G

Class III, Divisions 1 & 2

NEMA 3R, 4, 7 (B, C, D), 9 (E, F, G)

Detect up to 150 Feet

Recognize up to 75 Feet

Identify Individuals up to 50 Feet

Special Orders/Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EXPCMR-NDAA-IP-POE-4MP-IR Network Explosion Proof Camera from Larson Electronics is a remote inspection camera specifically designed for

observation in hazardous locations. This explosion proof, dust/ignition proof, weather proof and tamper resistant camera provides the operator with a live feed from inside tanks, reactors, vessels or other hazardous locations. Equipped with built-in infrared, this NDAA compliant remote inspection camera saves both time and money as well as contributing to workplace safety.

Camera Features: The EXPCMR-NDAA-IP-POE-4MP-IR Network Explosion Proof Camera features a built-in 1/3" progressive-scan CMOS image sensor that delivers up to 4.0MP resolution at 20 fps. The fixed lens with 80.8° of horizontal coverage and 45° of vertical coverage is designed to cover large areas and work spaces. This explosion proof camera provides a crisp and clear image for everything within the focal area. Total distance is dependent on mounting height and angle. This outdoor security camera complies with the 2019 National Defense Authorization Act (NDAA). The regulation bans federal governments, their contractors and businesses with national security interests from buying and using surveillance equipment made by specific major China-based manufacturers, including Hikvision, Dahua and their OEMs. Security products sold by Honeywell, Bosch, Panasonic, ADT, Flir and many more are affected by the ban. NDAA compliance also includes a ban on ZTE, Huawei and Hytera telecommunication equipment.

The explosion proof unit comes with built-in infrared lights. For additional infrared illumination, an external infrared light can be used with the explosion proof device (not included). For 12-24V DC applications, we recommend the Larson Electronics 12-watt explosion surface-mount infrared LED light ([EXHL-TRN-LE3-IR-1224](#)). As an alternative, we also offer the [EXHL-TRN-LE3-IR-1227](#) for 120-240V AC applications

This remote inspection camera utilizes a day/night IR-cut filter with auto switch (ICR) to produce clear images in variable and low light conditions. The camera automatically switches from full color to IR mode when visible light falls below a certain level.

Wiring: Link-up with the camera is achieved via a customer provided RJ45 Ethernet cable which is ran back to the customer provided DVR system mounted outside the hazardous location. Camera power is delivered via the same Ethernet cable using Power over Ethernet (PoE) technology. This not only increases flexibility in deployment, but also provides time and cost savings as well.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 - 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 - 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Recording: To record the stream from this camera, a NVR (network video recorder) is required. Larson Electronics provides a line of explosion proof, hazardous location, and non-classified NVR's to work in conjunction with this explosion proof camera. This camera is live-view capable without any NVR system via remote access to the camera. Three streams are available, one main stream for recording and two sub streams for live viewing or additional resources. Each stream can be configured to different resolutions and frame rates.

Mounting: The EXPCMR-NDAA-IP-POE-4MP-IR Network Explosion Proof Camera features an ATEX/IECEx certified copper-free aluminum alloy body. The camera includes an adjustable rear-mounted polished stainless steel mounting bracket/handle. Additional accessory pole mounts and magnetic mounts are available separately.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, monitoring of cleaning, spray patterns, mixing, foaming,


reaction, and level.


At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.




Frequently Asked Questions (FAQ)









Links (Click on the below items to view):

- [ATEX Certificate \(European Explosion Proof\)](#)
- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [Certificate 4, Misc](#)
- [Eye Safety Information/Certificate](#)
- [IEC Ex Certificate \(International Explosion Proof\)](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [STEP File \(3D CAD Model\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)