

## Solar Power LED Explosion Proof Light - Magnetic Surface Mount - Explosion Proof Inline Switch

### EXPLED-SOL12-M-SW.M-10C

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



#### EXPLED-SOL12-M-SW.M-10C Solar Powered Explosion Proof Light

Unit Type: Solar Powered LED Light  
Solar Panel Dimensions: 14.3" x 27.89" x 3.19"  
Lamp Dimensions: 7.44" x 11.1"  
Panel Watts: 30  
Battery: (4) 8aH Sealed Lead Acid Batteries  
Charging Time: 5 Hours  
Runtime: 12 Hours  
Operation: Remote On/Off Switch  
Ambient Temp: -45°C to +55°C  
Panel Mounting: Flat Surface / Round/Square Pole  
Lamp Watts: 12  
Lamp Lumens: 1,260  
Lamp Temp Rating: T6 - All Voltage and Temperature Ranges  
Housing Material: Copper-free Aluminum Alloy  
Housing Finish: Baked Powder Epoxy Finish  
Wiring: 20' 12/2 SOOW Cord (light to panel), 10' 12/2 SOOW (Switch to Panel)  
Lamp Wiring Hub: 3/4" Threaded  
Lamp Mount: Flat Surface Magnetic Ceiling Mount  
Weight: 30 lbs

#### Ratings/Approvals

Class I, Div 1, Groups C, D  
Class I, Div 2, Groups A, B, C, D  
Class II, Div 2, Groups F, G  
NEMA 4X  
Suitable for Marine Environments  
Day/Night Sensor w/ On/Off Switch  
Explosion Proof Light Switch

#### Special Orders - Special Requirements

Contact us for special requirements  
Toll Free: 1-800-369-6671  
Intl: 1-214-616-6180  
Fax: 1-903-498-3364  
E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

The EXPLED-SOL12-M-SW.M-10C from Larson Electronics is a Solar Powered Explosion Proof LED Light that is an ideal lighting solution for remote areas and standalone applications where connection to external power is either impractical or unavailable. This unit is magnetically mounted and offers 12 hours of continuous operation per charge and has a built-in day/night sensor with on/off switch for efficient power usage. Also included is a magnetically mounted explosion proof switch to control light operation. When ordering the solar powered luminary, please select the preferred LED color and strobing pattern.

This explosion proof LED light is powered by two 8aH sealed lead acid batteries that are recharged by a 30-watt solar panel. Light output comes from a 12-watt LED lamp that produces 1,260 lumens. When fully charged, this luminary is capable of operating continuously for 12 hours. To ensure consistent operation during nighttime conditions, a built-in day/night feature, coupled with an on/off switch is available. The battery pack in the EXPLED-SOL12-M-SW.M-10C is contained within the solar panel, not the light. Illumination produced by the explosion proof LED light will cover an area approximately 55' L x 55' W when mounted 12 feet from the ground.

---

As with all solar powered equipment, charging time is affected by the amount of available ambient light. When ambient light levels drop below a certain level, such as on cloudy days, the unit will not recharge as quickly. A remote mount on/off switch activates/shuts off the solar panel according to the operator's preferences.

**Explosion Proof Inline Switch:** This explosion proof tumbler switch is ideal for operators seeking a high quality explosion proof switch rated for use in hazardous areas designated Class 1 Division 1 and Class 2 Division 1. The entire unit is constructed of malleable iron and contains an internal sealing chamber constructed of copper free aluminum. The switch has 0ft of SOOW cord coming off of the panel and works as a pendant remote on/off switch for the light.

**Durability:** This hazardous area light (lamp fixture only) is NRTL Certified to UL Listed for Class I Division 1 Groups C and D; Class I Division 2 Groups A, B, C and D; and Class II Division 2 Groups F and G. These lights are also compliant with NEMA 4X standards and marine-rated for use in salt water environments. The high power LED cluster is protected by an internal cooling fin array that reduces heat build up for longer LED life and higher light output consistency. An internal DIP switch allows operators to choose from steady on, single flash or double flash modes.

The housing is made of high strength copper-free aluminum alloy with a baked powder epoxy finish and is magnetically mounted with a flat surface magnetic mount consisting of (3) 200lb magnets. The fixture ships with 20 feet of 12/2 SOOW cable that connects the light and the panel, and custom lengths are available upon request. Please contact us for special requirements.

---

**Mounting**  
**Round Pole**

**Square Pole**

**Surface**

---

**LED Benefits:** Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

**Applications:** Chemical plants, oil refineries, wastewater facilities, solvent storage areas, food processing plants, emergency lighting, notification lighting and remote hazardous locations compatible with the unit.

**NOTE:** Larson Electronics has further upgraded the options available with this light. We expect the light to be mounted separately from the panel. This means the solar panel can be mounted in direct sunlight (not in the hazardous area) while the light is mounted in a hazardous area workspace. Standard installation for explosion proof lighting, including threaded rigid pipe to the LED light fixture and appropriate seal-offs, etc. are required.



At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.



---

## Frequently Asked Questions (FAQ)







**Options:**

**EXPLED-SOL12-M-SW.M-10C-LED Color-Pattern**

**Example: EXPLED-SOL12-M-SW.M-10C-RED-SF**

LED Color	
RED	-RED
AMBER	-AMB
WHITE	-WHT
BLUE	-BLU
GREEN	-GRN

Pattern	
SINGLE FLASH	-SF
DOUBLE FLASH	-DF
STEADY BURN	-STB



Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)