

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



GAU-ID-36-1L-UVC-SPF Fluorescent UV-C Strip Fixture

Lamp Type: (1) Shatterproof Fluorescent UV-C T8 Tube

Dimensions: 38"L x 2.75W" x 1.75"H

Weight: -

Voltage: 120-277 V AC 50/60Hz

Total Watts: 30W

UV Output: 13.1W

UV Irradiance: 107 $\mu\text{W}/\text{cm}^2$ @ 1 Meter

UV Wavelength: UV-C, 200nm - 280nm (254 nm)

Lamp Life Expectancy: 8,000+ Hours

Replacement Lamp: FRL-36-1X-T8-30W-UV-C-SPF

Beam Angle: 180°

Lighting Configuration: Flood Pattern

Ambient Temperature Rating: 0°F to +104°F

Materials: 22G Steel Housing, Polycarbonate Lens

Mount: Surface, Chain, or Double Stem

Socket Type: G13 Bi-Pin

Ratings/Approvals

Kills 99% of Viruses and Other Germs

Shatterproof Lamp

Special Orders - Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

E-mail: sales@larsonelectronics.com

The Larson Electronics GAU-ID-36-1L-UVC-SPF Fluorescent UV-C Strip Fixture is an excellent choice for germicidal and sanitation use. This 30-watt unit is equipped with one, 30-watt shatterproof fluorescent UV-C tube. Constructed of steel (housing) and polycarbonate (lens), the fluorescent strip fixture is compatible with universal 120-277 V AC voltages.

****Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores and bacteria.***

[Click here to learn more about UVC and the corona virus*](#)

The GAU-ID-36-1L-UVC-SPF is an energy efficient and powerful lighting solution for industrial facilities, general locations and more. This 30-watt fluorescent strip fixture is equipped with one of our shatterproof 30 watt fluorescent UV-C T8 G13 medium bi-pin tubes. The GAU-ID-36-1L-UVC-SPF offers 13.1 watts of output, within the 280nm-200nm UV-C range (254nm peak) and has an expected lifespan of 8,000+ hours.

The GAU-ID-36-1L-UVC-SPF operates on 120-277 V AC current and accepts 36" shatterproof fluorescent T8 tubes with G13 bi-pin ends.

The GAU-ID-36-1L-UVC-SPF is constructed of die-formed and embossed 22-gauge

steel, with a polycarbonate lens. For durability, the unit is finished with high reflectance, baked white enamel.

Mounting: The GAU-ID-36-1L-UVC-SPF is compatible with surface mounting, chain (hanging) and double-stem mounting configurations. For seamless installations, wiring knockouts are provided on the back and end of the housing. For continuous row mounting requirements, the end plate can be used as a coupler.

Applications: Warehouses, industrial work sites, loading bays, control rooms, general locations, gymnasiums, schools, commercial locations, offices, buildings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)



Links (Click on the below items to view):

- [Video4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)