

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



HAL-EMG-48-60W-ITG-LED HAZLOC Failsafe Lighting

Listing: United States - Canada

Dimensions: W-5.76" x L-51" x H-3.92"

Weight: 32.9 Lbs

Voltage: Universal 120-277V AC 50/60 Hz

Total Watts: 60 watts

Total Lumens: 7,064

LED Lamp Life Expectancy: 60,000+ Hours

Luminous Efficacy: 117 Lumens per Watt

Color Temp: 5000K

Color Rendering Index: >70

Beam Angle: 160°

Battery AC Input Voltage: 120/277V AC 60Hz

Illumination Time: 90+ Minutes

Battery Lifespan: 7 to 10 Years

Battery Recharge Time: 24 Hours

Ambient Operating Temp Range: -30° C to +65°C

Operating Temp Rating: T6 Rated

Minimum Operating Temp: -30°C

Maximum Case Temp: +65°C

Housing Material: Copper Free Extruded Aluminum

Lens Material: Impact Resistant Polycarbonate

Gasket Material: Temperature Rated Silicone

Mounting: Slot, Swivel, Wall or Ceiling Brackets, Beam Clamps

Wiring Hub: 1/2" NPT

Ratings/Approvals

Class I, Division 2, Groups A, B, C, D

Class I, Zone 2, Groups IIC, IIB, IIA

Class II, Divisions 1 & 2, Groups E, F & G

UL 844 for Hazardous Locations

ANSI/UL 1598(A) Marine Type (Saltwater)

UL 8750 for LED Lighting

UL 924 for Emergency Lighting

CSA C22.2 No. 137-M1981

IEC Certified for Zone 2 & Zone 21

AEx nAII, Ex nAII

Ex nA IIC T6 to T3, Gc

Ex tb IIC T95°C Db

Tamb -50°C = Tz = +65°C

ATEX Certified

ABS Approved

IP66 Waterproof

NEMA 3, 4X

Approved for Confined Spaces

No Glass - Group G - Food Suitable

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The Larson Electronics HAL-EMG-48-60W-ITG-LED 60 Watt Explosion Proof Linear LED Emergency Light with 90 minute battery backup has a T6 temperature rating and is approved Class 1 Division 2 and Class 2 Division 1 & 2. This durable and long-lasting explosion proof LED light is designed for installation in locations where flammable vapors and gases and combustible dusts and fibers exist or have the potential to exist as well as NEMA 3, 4X, IP66 locations where wind, water, snow, or high ambients can be expected

The Larson Electronics HAL-EMG-48-60W-ITG-LED 60 Watt Explosion Proof Linear LED Emergency Light generates almost double the lumens of a standard fluorescent fixture and provides crisp white light and high chromaticity for excellent color rendering but uses significantly less energy and produces less heat than fluorescent lighting. Measuring only 3.92" tall and 4.25' long and weighing

less than 40 lbs, this extremely low profile 60 watt LED fixture delivers 7,064 lumens while drawing only 0.50 amps on 120 volts (though it is compatible with all 120-277 VAC 50/60Hz). The HAL-EMG-48-60W-ITG-LED produces both more light output and superior quality light than traditional fluorescent lighting fixtures while at the same time offering substantially reduced energy use and increased reliability, longevity, and safety.

Unlike the glass tube design of traditional fluorescent lamps, these LED explosion proof linear lamps have no filaments or fragile housings to break during operation. Instead of using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than fluorescent lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state LED design of the Larson Electronics HAL-EMG-48-60W-ITG-LED provides 212,000 hours of maintenance free operation before reducing to 70% of the original output, making it an altogether more reliable, stable, durable, cost-effective, and energy efficient light source over traditional fluorescent lighting.

The 60 watt LED is protected by a single impact and vibration resistant polycarbonate lens with a diffuse finish to reduce glare, and the LED assembly is housed within a low profile one piece copper-free extruded aluminum body designed to withstand hazardous and harsh conditions. A one wiring access plate makes for easy access to driver lead, and high temperature rated silicone gasketing between the lens and the housing provides NEMA 4X and IP66 sealing. Both the housing and the external screws are constructed to resist moisture, corrosion, ingress of dust and particles as well as being vibration and weather resistant. In addition to the rugged lens and body, the HAL-EMG-48-60W-ITG-LED comes equipped with supplemental 20kA/10kA surge protection and a 90 minute internal emergency battery backup.

The HAL-EMG-48-60W-ITG-LED is designed to accommodate a variety of mounting options include swivel brackets, wall and ceiling brackets, or beam clamps. The slot back design of the lamp allows multiple mounting access points across the length of the lamp. These slots can be used with 5/16" or 8mm bolts and nuts, three housing slots, one center back, and two at 45°. The end caps of the fixture each have two mounting feet built in, plus a safety strap attachment point. Additionally, each end cap features a 3/4" NPT hub, and the fixture comes furnished with one 3/4" close-up plug and two 3/4" to 1/2" reducers which provide 1/2" dead-end to 3/4" feed through flexibility.

The Larson Electronics HAL-EMG-48-60W-ITG-LED 60 Watt Explosion Proof Linear LED Emergency Light is a tough, durable, and low to no maintenance alternative to traditional fluorescent lighting. Its versatile power and mounting options, extreme longevity, low energy consumption, high light output, ultra low profile, and rugged lens and body design make it ideal for a variety of applications including, but not limited to: both land based oil rigs and offshore oil platforms, chemical and petrochemical processing facilities, sewage treatment plants, garages, storage facilities, tunnels, and grain/food facilities. In addition, the HAL-EMG-48-60W-ITG-LED carries ABS type approval for marine applications including use on decks, vessels, platforms, barges, ships, boats, and is suitable for dock and marina operations.

Suggested Applications:

Paint spray booths, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, gas processing plants, chemical manufacturing, waste treatment plants, gas processing plants.

Made in USA Quality

1. Each unit dielectrically tested.
2. Fixture arrives assembled to reduce installation time and

Superior LED Benefits

1. 212,000 hour lifespan.
2. Can SAVE 50% or more on energy.

cost. Flexible mounting options enable the operator to choose any mounting angle for the fixture.

3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy
4. No ballast box. No ballast to replace.
5. Heavy gauge extruded aluminum with high gloss reflective finish. Resists dents and corrosion.
6. Easy access to wiring hubs.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.



Frequently Asked Questions (FAQ)

Warranty: 60 Months



Links (Click on the below items to view):

- [ISO 9001 Certification](#)
- [Business Certificate](#)